



### Overview

Leveringstid Usually in Stock



### General

Inkludert utstyr	Brukermanual
Performance multiplier	1
Number of power module	210
Number of tare power	38 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Workstation
UPS size	WS
Value multiplier	1

### Physical

Kabellengde	1,83 m
Farge	Charcoal
Dybde	9,5 cm
Høyde	11,5 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	4 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	36 cm

### Input

Network frequency	50 Hz +/- 3 Hz
Plug standard	Schuko CEE 7/7P
Input voltage limits	180...266 V
Maximum input current	4 A
Brytekapasitet, A	4 A

Antall kabler	1
Forsyningsspenning	230 V

## Output

Merkeeffekt i W	185 W
Maximum configurable power in W	185 W
Output frequency	47...63 Hz sync to mains
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	2 Schuko CEE 7 2 Schuko CEE 7 surge
Curve equation	Efficiency
Curve fixed loss	0,0455
Curve load maximum	100 %
Curve load minimum	5 %
Curve proportional loss	0
Curve square loss	0,002
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Maximum output current	4 A
Output voltage	230 V
Maximum configurable power in VA	325 VA
Merkeeffekt VA	325 VA
Transfer time	4 ms typical : 8 ms maximum

## Conformance

Produktsertifikater	CE NEMKO
Merking	GS Mark
Standarder	EN 50091-1 EN 50091-2
Equipment protection policy	Lifetime : 75000 euros

## Environmental

Omgivestemperatur drift	0...40 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivestemperatur for lagring	-15...45 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Varmeavgivelse	31 Btu/t
Show note OP temperature	No

## Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	24 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	3,0 Ah
Battery curve	B
Battery charger power	2 W rated
Battery power in VAH	43 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

## Communications & Management

Ledige plasser	0
Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

## Surge Protection and Filtering

Surge energy rate	310 J
Data line protection	RJ11 modem/fax/DSL protection (two wire single line)

## Packing Units

Forpakning 1 vekt	4,6 kg
Forpakning 1 høyde	15,3 cm
Forpakning 1 bredde	46,5 cm
Forpakning 1 lengde	11,6 cm
SCC14	10731304211140
Antall enheter forpakning 2	1
Forpakning 2 vekt	18,76 kg
Forpakning 2 lengde	245,11 mm
Antall enheter forpakning 3	64

## Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	<a href="#">REACH-erklæring</a>
EU RoHS-direktiv	I samsvar <a href="#">EU RoHS-erklæring</a>
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	<a href="#">Ja</a>
Miljøinformasjon	<a href="#">Produktmiljøprofil</a>
Produktets livssyklus	<a href="#">Informasjon Om Levetidsslutt</a>
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

## Contractual warranty

Garanti	3 years repair or replace
---------	---------------------------