

Mer om BE400-GR

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



BE400-GR

APC Back-UPS 400, 230V, German & Dutch

EI-nummer: 6605201

EAN: 0731304233367



by Schneider Electric



 Last ned produktdatablad for BE400-GR

Karakteristikk

Overview

Leveringstid Usually in Stock

General

Inkludert utstyr User manual
Wall-mounting template

Performance multiplier 1

Number of tare power 24 W

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

Size UPS version Workstation

UPS size WS

Value multiplier 1

Physical

Kabellengde 1,83 m

Farge Charcoal

Dybde 28,5 cm

Høyde 8,6 cm

Montasjeplassering Front

Mounting preference No preference

Vekt 5,4 kg

Monteringsmetode Not rack-mountable

Two post mountable 0

USB compatible No

Bredde 23 cm

Input

Network frequency 50/60 Hz

Plug standard Schuko CEE 7/7P

Input voltage limits 180...266 V

Maximum input current	10 A
Brytekapasitet, A	10 A
Antall kabler	1
Forsyningsspenning	230 V
Output	
Merkeeffekt i W	240 W
Maximum configurable power in W	240 W
Output frequency	47...63 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 Schuko CEE 7 4 Schuko CEE 7 surge
Curve equation	Efficiency
Curve fixed loss	0,0118
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0,001
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	400 VA
Merkeeffekt VA	400 VA
Transfer time	6 ms typical : 10 ms maximum
Conformance	
Produktsertifikater	CE GOST NEMKO
Equipment protection policy	Lifetime : 100000 euros
Environmental	

Omgivelsestemperatur drift	0..40 °C
Relativ fuktighet	0..95 %
Driftshøyde	0..50000 ft
Omgivelsestemperatur for lagring	0..40 °C
Storage Relative Humidity	0..95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	6,0 Ah
Battery curve	A
Battery charger power	6 W rated
Battery power in VAH	102 VAh runtime
Batterilevetid	2..5 år
Extended runtime	0

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ11 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100 base-T Ethernet

Packing Units

Forpakning 1 vekt	5,6 kg
Forpakning 1 høyde	13,2 cm
Forpakning 1 bredde	30 cm
Forpakning 1 lengde	36,6 cm
SCC14	10731304233364
Antall enheter forpakning 2	2
Forpakning 2 vekt	12,17 kg
Forpakning 2 lengde	381,00 mm

Antall enheter forpakning 3	48
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
Contractual warranty	
Garanti	2 years repair or replace, 3 years repair or replace for European Union countries