



### Teknisk informasjon

Serie	ComPacT new generation
Produktspekter	ComPacT NSX100...250 new generation
Produkt eller type komponent	Vern
Navn på vern	Micrologic 2.2 M
Vernteknologi	Elektronisk
Kompatibel med	ComPacT new generation NSX100 ComPacT new generation NSX160 ComPacT new generation NSX250
Applikasjon	Motor
Antall poler	3P
Polbeskrivelse	3t
Vernfunksjoner	LSol
Beskyttelsestype	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip unit rating	100 A på 65 °C
[Ue] merkespenning	690 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Circuit breaker mounting mode	Fast

### Komplementær

Motorstarterklasse	20 10 5
Tilleggsbeskyttelse for motorer	Faseubalanse
Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	50...100 A
Long-time protection delay adjustment type tr	Fast
[tr] long-time protection delay adjustment range	120 S at 1.5 x Ir for trip class 5 6.5 S at 6 x Ir for trip class 5 5 S at 7.2 x Ir for trip class 5 240 S at 1.5 x Ir for trip class 10 13.5 S at 6 x Ir for trip class 10 10 S at 7.2 x Ir for trip class 10 480 S at 1.5 x Ir for trip class 20 26 S at 6 x Ir for trip class 20 20 s at 7.2 x Ir for trip class 20
Termisk minne	20 min før og etter utkobling
Short-time protection pick-up adjustment type Isd	Justerbar 9 innstillinger
[Isd] Short-time protection pick-up adjustment range	5...13 x Ir
Short-time protection delay adjustment type tsd	Fast
[tsd] Short-time protection delay adjustment range	0,01 s
Instantaneous protection pick-up adjustment type Ii	Fast
[Ii] instantaneous protection pick-up adjustment range	1500 A
Jordfeilbeskyttelse	Uten
Lokal varsling	Flashing LED (green) for ready to operate LED 95 % lth (red) for temperature over set point

## Miljø

Standarder	EN/IEC 60947-2 UL 508
Produktsertifikater	EAC CCC Marine
Forurensninggrad	3 conforming to IEC 60947-1
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-50...85 °C

## Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	437 g
Forpakning 1 høyde	6,6 cm
Forpakning 1 bredde	9,6 cm
Forpakning 1 lengde	11,2 cm

## Offer Sustainability

REACH-regelverk	<a href="#">REACH-erklæring</a>
EU RoHS-direktiv	I samsvar <a href="#">EU RoHS-erklæring</a>
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	<a href="#">Ja</a>
Kinas RoHS-forskrift	<a href="#">Kinas RoHS-Erklæring</a>

## Contractual warranty

Garanti	18 måneder
---------	------------