

C10N4TM016

Effektbryter ComPacT NSX med termomagnetisk vern NSX100N-TM16D 4P4T 16A 50kA/415VAC - 90kA/230VAC



Teknisk informasjon

Serie	ComPacT new generation
Produktnavn	ComPacT NSX new generation
Produktspekter	ComPacT NSX100...250 new generation
Kortnavn utstyr	NSX100N
Produkt eller type komponent	Effektbryter
Applikasjon	Distribusjon
Antall poler	4P
Polbeskrivelse	4t
Plassering av nøytral	VENSTRE
[In] merkestrøm	16 A på 40 °C
[Ue] merkespenning	690 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Egnethet for isolasjon	Ja i samsvar med EN/IEC 60947-2
Driftskategori	Kategori A
[Icu] rated ultimate short-circuit breaking capacity	85 KA på 240 V AC 50/60 Hz i samsvar med UL 508 10 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 20 KA på 600 V AC 50/60 Hz i samsvar med UL 508 50 KA at 480 V AC 50/60 Hz conforming to UL 508 36 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	N 50 kA 415 V AC
Navn på vern	TM-D
Vernteknologi	Termisk-magnetisk
Vernfunksjoner	LI
Kontrolltype	Kipp
Circuit breaker mounting mode	Fast

Komplementær

[Ui] isolasjonsspenning	800 V AC 50/60 Hz
[Uimp] Nominell impuls-spenning	8 kV
[Ics] rated service short-circuit breaking capacity	10 KA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2 36 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Mekanisk levetid	50000 sykluser
Elektrisk levetid	10000 Cycles at 690 V In 20000 Cycles at 690 V In/2 30000 Cycles at 440 V In 50000 cycles at 440 V In/2

Power losses	2,92 W
Montering	Bakplate
Tilkobling oppe	Front
Tilkobling i bunn	Front
Connection pitch	35 mm
Beskyttelsestype	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Vernstørrelse	16 A at 40 °C
Long-time pick-up adjustment type I _r (thermal protection)	Justerbar
[I _r] long-time protection pick-up adjustment range	0.7...1 x I _n
Long-time protection delay adjustment type t _r	Fast
[t _r] long-time protection delay adjustment range	120...400 S at 1.5 x I _n 15 s at 6 x I _r
Short-time protection pick-up adjustment type I _{sd}	Fast
[I _{sd}] Short-time protection pick-up adjustment range	190 A
Short-time protection delay adjustment type t _{sd}	Fast
Jordfeilbeskyttelse	Uten
Neutral protection settings	1 x I _r (4t)
Number of slots for electrical auxiliaries	5 slot(s)
Width (W)	140 mm
Height (H)	161 mm
Depth (D)	86 mm
Vekt	2,4 kg

Miljø

Standarder	EN/IEC 60947
Produktsertifikater	CCC EAC Marine
Overspenningskategori	Klasse II
Beskyttelsesklasse for elektrisk støt	Klasse II
Forurensningsgrad	3 i samsvar med IEC 60664-1
IP-grad	IP40 i samsvar med IEC 60529
IK beskyttelsesklasse	IK07 i samsvar med IEC 62262
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-50...85 °C
Relativ fuktighet	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	2,447 kg
Forpakning 1 høyde	15 cm
Forpakning 1 bredde	18 cm
Forpakning 1 lengde	19 cm

Offer Sustainability

REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring

Contractual warranty

Garanti

18 måneder
