

C11B4TM100B

Effektbryter ComPacT NSXm B 50kA/230V 25kA/400V-med termomagnetisk vern-TM100D 4p bolt 100A



Teknisk informasjon

Serie	ComPacT new generation
Produktnavn	ComPacT NSXm new generation
Produktspekter	ComPacT NSXm new generation
Kortnavn utstyr	NSXm 100B
Produkt eller type komponent	Effektbryter
Applikasjon	Distribusjon Beskyttelse
Antall poler	4P
Polbeskrivelse	4d
Plassering av nøytral	VENSTRE
[In] merkestrøm	100 A at 40 °C
[Ue] merkespenning	690 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Egnethet for isolasjon	Ja i samsvar med IEC 60947-2
Driftskategori	Kategori A
[Icu] rated ultimate short-circuit breaking capacity	50 KA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 25 KA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	B 25 kA 415 V AC
Navn på vern	TM-D
Vernteknologi	Termisk-magnetisk
Vernfunksjoner	LI
Kontrolltype	Kipp
Circuit breaker mounting mode	Fast

Komplementær

[Ui] isolasjonsspenning	800 V
[Uimp] Nominell impuls-spenning	8 kV
[Ics] rated service short-circuit breaking capacity	50 KA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 25 KA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2
Mekanisk levetid	20000 sykluser
Elektrisk levetid	20000 Cycles at 440 V In/2 10000 Cycles at 440 V In 10000 Cycles at 690 V In/2 5000 cycles at 690 V In
Power losses	8,77 W
Montering	Bakplate
Tilkobling oppe	Front
Tilkobling i bunn	Front
Connection terminals	Compression lug/busbar
Connection pitch	35 Mm with spreaders 27 mm without spreaders
Access by modem	12 module

Vernstørrelse	100 A at 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Justerbar
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fast
[Im] magnetic protection pick-up range	1500 A
Short-time protection pick-up adjustment type Isd	Fast
Short-time protection delay adjustment type tsd	Fast
Number of slots for electrical auxiliaries	1 slot(s) for auxiliary switch OF 1 slot(s) for alarm switch SD 1 slot(s) for voltage release MN or MX
Lokal varsling	Flag (green) for presence of auxiliary contacts
Width (W)	108 mm
Height (H)	137 mm
Depth (D)	80 mm
Vekt	1,42 kg
Antall pr. sett	Sett á 1
Farge	Grey (RAL 7016)

Miljø

Standarder	EN/IEC 60947
Forurensningsgrad	3 i samsvar med IEC 60664-1
IP-grad	IP40
IK beskyttelsesklasse	IK07 conforming to IEC 62262
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-50...85 °C
Operating altitude	2000 m without derating 5000 m with derating

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	1,6 kg
Forpakning 1 høyde	12 cm
Forpakning 1 bredde	13 cm
Forpakning 1 lengde	22 cm
Enhetstype forpakning 2	S03
Antall enheter forpakning 2	6
Forpakning 2 vekt	10,19 kg
Forpakning 2 høyde	30 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm

Offer Sustainability

REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring

Contractual warranty

Garanti	18 måneder
---------	------------