



Teknisk informasjon

Serie	ComPacT new generation
Produktspekter	ComPacT NSX100...250 new generation
Produkt eller type komponent	Vern
Navn på vern	Micrologic 4.2 AL
Vernteknologi	Elektronisk
Kompatibel med	ComPacT new generation NSX160 ComPacT new generation NSX250
Applikasjon	Distribusjon
Antall poler	4P
Polbeskrivelse	4t 3t + N/2 3t
Vernfunksjoner	LSol
Beskyttelsestype	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip unit rating	160 A på 40 °C
[Ue] merkespenning	440 V AC 50/60 Hz
Type nettverk	AC
Nettverksfrekvens	50/60 Hz
Circuit breaker mounting mode	Fast

Komplementær

Long-time pick-up adjustment type Ir (thermal protection)	Justerbar 9 innstillinger
[Ir] long-time protection pick-up adjustment range	0.4...1 x In
Long-time protection delay adjustment type tr	Fast
[tr] long-time protection delay adjustment range	11 S at 7.2 x Ir 16 S at 6 x Ir 400 s at 1.5 x Ir
Termisk minne	20 min før og etter utkobling
Short-time protection pick-up adjustment type Isd	Justerbar
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Fast
[tsd] Short-time protection delay adjustment range	0,02 s
Instantaneous protection pick-up adjustment type Ii	Fast
[Ii] instantaneous protection pick-up adjustment range	2400 A
Jordfeilbeskyttelse	Integrert
Jordfeilvern klasse	Type A
[IΔn] earth-leakage protection sensitivity adjustment range	500 MA 3 A 100 MA 30 MA 1 A 5 A 300 mA
Earth-leakage protection specific mode	AV using the IΔn rotary switch

Earth-leakage protection time delay adjustment type Δt	Justerbar
[Δt] Earth-leakage protection time delay adjustment range	150 Ms 60 Ms 500 Ms 0 Ms 1 s
Zone selektiv forrigling (logisk selektivitet) ZSI	Uten
Lokal varslng	Flashing LED (green) for ready to operate LED 105 % I _r (red) for overload LED 90 % I _r (orange) for overload Residual current: color indicator (gul)

Miljø

Standarder	EN 60947-2 UL 508 IEC 60947-2 Nema AB1
Produktsertifikater	CB EAC CCC
Forurensninggrad	3 conforming to IEC 60947-1
IP-grad	IP40 i samsvar med IEC 60529
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-40...85 °C

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	770 g
Forpakning 1 høyde	9,5 cm
Forpakning 1 bredde	11 cm
Forpakning 1 lengde	15 cm
Enhetstype forpakning 2	S03
Antall enheter forpakning 2	10
Forpakning 2 vekt	8,098 kg
Forpakning 2 høyde	30 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm

Offer Sustainability

REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-Erklæring

Contractual warranty

Garanti	18 måneder
---------	------------