

Mer om LC1D12BD

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**LC1D12BD**

LC1D: 3-polede kontaktorer med DC-spole til motordrift og ikke-induktive belastn

EI-nummer: 4176594

EAN: 3389110353716



Last ned produktdatablad for LC1D12BD 3D CAD Modell

Karakteristikk

Teknisk informasjon

Serie	TeSys
Produktnavn	TeSys D
Produkt eller type komponent	Kontaktor
Kortnavn utstyr	LC1D
Contactor application	Omsk last Motor control
Driftskategori	AC-1 AC-4 AC-3
Antall poler	3P
Power pole contact composition	3 NO
[U _e] merkespenning	Power circuit: ≤ 690 V AC 25...400 Hz Power circuit: ≤ 300 V DC
[I _e] nominell driftsstrøm	25 A (at <60 °C) at ≤ 440 V AC AC-1 for power circuit 12 A (at <60 °C) at ≤ 440 V AC AC-3 for power circuit
Motoreffekt kW	3 kW at 220...230 V AC 50/60 Hz (AC-3) 5.5 kW at 380...400 V AC 50/60 Hz (AC-3) 5.5 kW at 415...440 V AC 50/60 Hz (AC-3) 7.5 kW at 500 V AC 50/60 Hz (AC-3) 7.5 kW at 660...690 V AC 50/60 Hz (AC-3) 3.7 kW at 400 V AC 50/60 Hz (AC-4)
Motor power HP (UL / CSA)	0.5 hp at 115 V AC 50/60 Hz for 1 phase motors 2 hp at 230/240 V AC 50/60 Hz for 1 phase motors 3 hp at 200/208 V AC 50/60 Hz for 3 phases motors 3 hp at 230/240 V AC 50/60 Hz for 3 phases motors 7.5 hp at 460/480 V AC 50/60 Hz for 3 phases motors 10 hp at 575/600 V AC 50/60 Hz for 3 phases motors
Kontrollkretstype	DC standard
Styrespenning	24 V DC
Hjelpkontakt sammensetning	1 NO + 1 NC
[U _{imp}] Nominell impuls spenning	6 kV conforming to IEC 60947
Overspenningskategori	III

[I_{th}] fri luft termisk strøm	25 A (at 60 °C) for power circuit 10 A (at 60 °C) for signalling circuit
I_{rms} rated making capacity	250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	250 A at 440 V for power circuit conforming to IEC 60947
[I_{cw}] kort-tids/kortslutnings merkestrøm	105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Sikringsstørrelse	10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at ≤ 690 V coordination type 1 for power circuit 25 A gG at ≤ 690 V coordination type 2 for power circuit
Gjennomsnittlig impedanse	2.5 mOhm - I _{th} 25 A 50 Hz for power circuit
[U_i] isolasjonsspenning	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified
Elektrisk levetid	2 Mcycles 12 A AC-3 at U _e ≤ 440 V 0.8 Mcycles 25 A AC-1 at U _e ≤ 440 V
Power dissipation per pole	0.36 W AC-3 1.56 W AC-1
Front cover	Med
Montering	Plate Skinne
Standarder	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Produktsertifikater	BV CSA DNV RINA GL GOST LROS (Lloyds register of shipping) CCC UL UKCA

Tilkoblingsklemmer	<p>Power circuit: screw clamp terminals 1 cable(s) 1..4 mm²flexible without cable end</p> <p>Power circuit: screw clamp terminals 2 cable(s) 1..4 mm²flexible without cable end</p> <p>Power circuit: screw clamp terminals 1 cable(s) 1..4 mm²flexible with cable end</p> <p>Power circuit: screw clamp terminals 2 cable(s) 1..2.5 mm²flexible with cable end</p> <p>Power circuit: screw clamp terminals 1 cable(s) 1..4 mm²solid without cable end</p> <p>Power circuit: screw clamp terminals 2 cable(s) 1..4 mm²solid without cable end</p> <p>Control circuit: screw clamp terminals 1 cable(s) 1..4 mm²flexible without cable end</p> <p>Control circuit: screw clamp terminals 2 cable(s) 1..4 mm²flexible without cable end</p> <p>Control circuit: screw clamp terminals 1 cable(s) 1..4 mm²flexible with cable end</p> <p>Control circuit: screw clamp terminals 2 cable(s) 1..2.5 mm²flexible with cable end</p> <p>Control circuit: screw clamp terminals 1 cable(s) 1..4 mm²solid without cable end</p> <p>Control circuit: screw clamp terminals 2 cable(s) 1..4 mm²solid without cable end</p>
Tiltrekningsmoment	<p>Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm</p> <p>Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2</p> <p>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm</p> <p>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2</p>
Driftstid	53.55...72.45 ms closing 16...24 ms opening
Sikkerhet pålitelighet nivå	<p>B10d = 1369863 cycles contactor with nominal load conforming to ENISO 13849-1</p> <p>B10d = 20000000 cycles contactor with mechanical load conforming to ENISO 13849-1</p>
Mekanisk levetid	30 Mcycles
Bruksområde	3600 cyc/h 60 °C
Komplementær	
Spiral teknologi	With integral suppression device
Control circuit voltage limits	0.1...0.25 U _c (-40...70 °C):drop-out DC 0.7...1.25 U _c (-40...60 °C):operational DC 1...1.25 U _c (60...70 °C):operational DC
Tidskonstant	28 ms
Inrush power in W	5.4 W(at 20 °C)
Hold-in strømforbruk i W	5.4 W at 20 °C
Auxiliary contacts type	Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 Type mirror contact 1 NC conforming to IEC 60947-4-1
Signale krets frekvens	25...400 Hz
Minimum brytestrøm	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Isolasjonsmotstand	> 10 MOhm for signalling circuit
Miljø	

IP-grad	IP20 front face conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068-2-30
Forurensninggrad	3
Omgivelsestemperatur for drift	-40...60 °C 60...70 °C with derating
Omgivelsestemperatur for lagring	-60...80 °C
Operating altitude	0...3000 m
Brannmotstand	850 °C conforming to IEC 60695-2-1
Flammehemming	V1 conforming to UL 94
Mekanisk robusthet	Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 4 Gn, 5...300 Hz Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms
Høyde	77 mm
Bredde	45 mm
Dybde	95 mm
Vekt	0,485 kg
Packing Units	
Enhetsstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	520,25 g
Forpakning 1 høyde	5 cm
Forpakning 1 bredde	9 cm
Forpakning 1 lengde	11 cm
Enhetsstype forpakning 2	S02
Antall enheter forpakning 2	15
Forpakning 2 vekt	8,039 kg
Forpakning 2 høyde	15 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm
Enhetsstype forpakning 3	P06
Antall enheter forpakning 3	240
Forpakning 3 vekt	136,624 kg
Forpakning 3 høyde	75 cm
Forpakning 3 bredde	80 cm
Forpakning 3 lengde	60 cm
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja

Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
PVC-fri	Ja
Contractual warranty	
Garanti	18 months