

Mer om LC1D18M7

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



LC1D18M7

Kontaktor 18A 3P 220VAC

EI-nummer: 4177269

EAN: 3389110349504



Last ned produktdatablad for LC1D18M7 3D CAD Modell

Karakteristikk

Teknisk informasjon

Serie	TeSys
Produktnavn	TeSysD
Produkt eller type komponent	Kontaktor
Kortnavn utstyr	LC1D
Contactor application	Omsk last Motor control
Driftskategori	AC-1 AC-4 AC-3
Antall poler	3P
Power pole contact composition	3 NO
[Ue] merkespenning	Power circuit: ≤ 690 V AC 25...400 Hz Power circuit: ≤ 300 V DC
[Ie] nominell driftsstrøm	18 A (at <60 °C) at ≤ 440 V AC AC-3 for power circuit 32 A (at <60 °C) at ≤ 440 V AC AC-1 for power circuit
Motoreffekt kW	4 kW på 220...230 V AC 50/60 Hz (AC-3) 7,5 kW på 380...400 V AC 50/60 Hz (AC-3) 9 kW på 415...440 V AC 50/60 Hz (AC-3) 10 kW på 500 V AC 50/60 Hz (AC-3) 10 kW på 660...690 V AC 50/60 Hz (AC-3) 4 kW på 400V AC 50/60 Hz (AC-4)
Motor power HP (UL / CSA)	1 hp på 115 V AC 50/60 Hz for 1 fase 3 hp på 230/240 V AC 50/60 Hz for 1 fase 5 hp på 200/208 V AC 50/60 Hz for 3 faser 5 hp på 230/240 V AC 50/60 Hz for 3 faser 10 hp på 460/480 V AC 50/60 Hz for 3 faser 15 hp på 575/600 V AC 50/60 Hz for 3 faser
Kontrollkretstype	AC at 50/60 Hz
Styrespenning	220 V AC 50/60 Hz
Hjelpkontakt sammensetning	1 NO + 1 NC
[Uimp] Nominell impuls ­ spenning	6 kV conforming to IEC 60947
Overspenningskategori	III
[Ith] fri luft termisk strøm	10 A (at 60 °C) for signalling circuit 32 A (at 60 °C) for power circuit

Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 300 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	300 A at 440 V for power circuit conforming to IEC 60947
[Icw] kort-tids/kortslutnings merkestrøm	145 A 40 °C - 10 s for power circuit 240 A 40 °C - 1 s for power circuit 40 A 40 °C - 10 min for power circuit 84 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Sikringsstørrelse	10 A gG for signalling circuit conforming to IEC 60947-5-1 50 A gG at <= 690 V coordination type 1 for power circuit 35 A gG at <= 690 V coordination type 2 for power circuit
Gjennomsnittlig impedanse	2.5 mOhm - lth 32 A 50 Hz for power circuit
[Ui] isolasjonsspenning	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified
Elektrisk levetid	1.65 Mcycles 18 A AC-3 at Ue <= 440 V 1 Mcycles 32 A AC-1 at Ue <= 440 V
Power dissipation per pole	2.5 WAC-1 0.8 WAC-3
Front cover	Med
Montering	Plate Skinne
Standarder	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Produktsertifikater	GOST UL RINA CCC DNV BV GL CSA LROS (Lloyds register of shipping) UKCA

Tilkoblingsklemmer	Control circuit: screw clamp terminals 1 cable(s) 1..4 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1..4 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 1..4 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1..2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1..4 mm ² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1..4 mm ² solid without cable end Power circuit: screw clamp terminals 1 cable(s) 1.5..6 mm ² flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 1.5..6 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 1..6 mm ² flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 1..4 mm ² flexible with cable end Hovedstrøm: skrutilkobling 1 kabel (kabler) 1,5... 6 mm ² solid uten Hovedstrøm: skrutilkobling 2 kabel (kabler) 1,5... 6 mm ² solid uten
Tiltrekningsmoment	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
Driftstid	12...22 ms closing 4...19 ms opening
Sikkerhet pålitelighet nivå	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mekanisk levetid	15 Mcycles
Bruksområde	3600 cyc/h 60 °C
Komplementær	
Spiral teknologi	Uten innebygd suppressor modul
Control circuit voltage limits	0.3...0.6 U _c (-40...70 °C):drop-out AC 50/60 Hz 0.8...1.1 U _c (-40...60 °C):operational AC 50 Hz 0.85...1.1 U _c (-40...60 °C):operational AC 60 Hz 1...1.1 U _c (60...70 °C):operational AC 50/60 Hz
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C)
Hold-in strømforbruk i VA	7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C)
Varmeavgivelse	2..3 W at 50/60 Hz
Auxiliary contacts type	Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 Type mirror contact 1 NC conforming to IEC 60947-4-1
Signale krets frekvens	25...400 Hz
Minimum brytestrøm	5 mA for signalling circuit
Minimum switching v voltage	17 V for signalling circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact

Isolasjonsmotstand	> 10 MOhm for signalling circuit
--------------------	----------------------------------

Miljø

IP-grad	IP20 front face conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068-2-30
Forurensninggrad	3
Omgivelsestemperatur for drift	-40...60 °C 60...70 °C with derating
Omgivelsestemperatur for lagring	-60...80 °C
Operating altitude	0...3000 m
Brannmotstand	850 °C conforming to IEC 60695-2-1
Flammehemming	V1 conforming to UL 94
Mekanisk robusthet	Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 4 Gn, 5...300 Hz Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms
Høyde	77 mm
Bredde	45 mm
Dybde	86 mm
Vekt	0,33 kg

Packing Units

Enhetsstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	351,95 g
Forpakning 1 høyde	5 cm
Forpakning 1 bredde	9 cm
Forpakning 1 lengde	11,3 cm
Enhetsstype forpakning 2	S02
Antall enheter forpakning 2	20
Forpakning 2 vekt	7,415 kg
Forpakning 2 høyde	15 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm
Enhetsstype forpakning 3	P06
Antall enheter forpakning 3	320
Forpakning 3 vekt	128,42 kg
Forpakning 3 høyde	80 cm
Forpakning 3 bredde	80 cm
Forpakning 3 lengde	60 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
REACH fri for SVHC	Ja

EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
PVC-fri	Ja
Contractual warranty	
Garanti	18 months