

Mer om LC1K0901E7

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



LC1K0901E7

Kontaktor 9A 3P+1NC 48VAC

EI-nummer: 4172057

EAN: 3389110374759

Last ned produktdatablad for LC1K0901E7 3D CAD Modell

Karakteristikk

Teknisk informasjon

Serie	TeSys
Produkt eller type komponent	Kontaktor
Produktnavn	TeSysK
Kortnavn utstyr	LC1K
Applikasjon	Kontroll
Contactor application	Omsklast Motor control

Komplementær

Driftskategori	AC-4 AC-3 AC-1
Antall poler	3P
Power pole contact composition	3 NO
[Ue] merkespenning	Power circuit: 690 V AC 50/60 Hz Signalling circuit: ≤ 690 V AC 50/60 Hz
[Ie] nominell driftsstrøm	20 A (at 50°C) at ≤ 440 V AC AC-1 for power circuit 9 A at ≤ 440 V AC AC-3 for power circuit 16 A (at 70°C) at 690 V AC AC-1 for power circuit
Kontrollkretstype	AC på 50/60 Hz
Styrespenning	48 V AC 50/60 Hz
Motoreffekt kW	2,2 kW på 220...230 V AC 50/60 Hz AC-3 4 kW på 380 - 415 V AC 50/60 Hz AC-3 4 kW på 440 V AC 50/60 Hz AC-3 4 kW på 480 V AC 50/60 Hz AC-3 4 kW på 500...600 V AC 50/60 Hz AC-3 4 kW på 660...690 V AC 50/60 Hz AC-3 2,2 kW på 400V AC 50/60 Hz AC-4
Hjelpkontakt sammensetning	1 NC
[Uimp] Nominell impuls ­ spenning	8 kV
Overspenningskategori	III
[Ith] fri luft termisk strøm	20 A (at 50°C) for power circuit 10 A (at 50°C) for signalling circuit

Irms rated making capacity	110 A AC for power circuit conforming to NF C 63-110 110 A AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947
Rated breaking capacity	110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 110 A at 220...230 V conforming to IEC 60947 110 A at 380...400 V conforming to IEC 60947 70 A at 660...690 V conforming to IEC 60947
[Icw] kort-tids/kortslutnings merkestrøm	90 A 50 °C - 1 s for power circuit 85 A 50 °C - 5 s for power circuit 80 A 50 °C - 10 s for power circuit 60 A 50 °C - 30 s for power circuit 45 A 50 °C - 1 min for power circuit 40 A 50 °C - 3 min for power circuit 20 A 50 °C - >= 15 min for power circuit 80 A - 1 s for signalling circuit 90 A - 500 ms for signalling circuit 110 A - 100 ms for signalling circuit
Sikringsstørrelse	25 A gG at <= 440 V for power circuit 25 A aM for power circuit 10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660
Gjennomsnittlig impedanse	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] isolasjonsspenning	Power circuit: 600 V conforming to UL 508 Power circuit: 690 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-5-1 Signalling circuit: 600 V conforming to UL 508 Power circuit: 600 V conforming to CSA C22.2 No 14 Signalling circuit: 600 V conforming to CSA C22.2 No 14
Isolasjonsmotstand	> 10 MOhm for signalling circuit
Inrush power in VA	30 VA (at 20 °C)
Hold-in strømforbruk i VA	4.5 VA (at 20 °C)
Varmeavgivelse	1.3 W
Control circuit voltage limits	Operational: 0.8...1.15 Uc (at <50 °C) Drop-out: 0.2...0.75 Uc (at <50 °C)
Tilkoblingsklemmer	Screw clamp terminals 1 cable(s) 1.5... 4 mm ² solid Screw clamp terminals 1 cable(s) 0.75... 4 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.34... 2.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 1.5... 4 mm ² solid Screw clamp terminals 2 cable(s) 0.75... 4 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.34... 1.5 mm ² flexible with cable end
Bruksområde	3600 cyc/h
Auxiliary contacts type	Type instantaneous 1 NC
Signale krets frekvens	<= 400 Hz
Minimum brytestrøm	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit

Montering	Skinne Plate
Tiltrekningsmoment	1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
Driftstid	10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing
Sikkerhet pålitelighet nivå	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Non overlapping av stand	0.5 mm
Mekanisk levetid	10 Mcycles
Elektrisk levetid	0.18 Mcycles 20 A AC-1 at Ue ≤ 440 V 1.3 Mcycles 9 A AC-3 at Ue ≤ 440 V
Mekanisk robusthet	Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations contactor closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6
Dybde	57 mm
Vekt	0,18 kg
Miljø	
Standarder	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Produktsertifikater	CSA UL
IP-grad	IP2x conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068 TC conforming to DIN 50016
Omgivelsestemperatur for lagring	-50...80 °C
Operating altitude	2000 m without derating
Flammehemming	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102
Packing Units	
Enhetsstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	180,083 g
Forpakning 1 høyde	4,8 cm
Forpakning 1 bredde	6,2 cm
Forpakning 1 lengde	6,5 cm

Enhetstype forpakning 2	S02
Antall enheter forpakning 2	50
Forpakning 2 vekt	9,264 kg
Forpakning 2 høyde	15 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm
Offer Sustainability	
REACH-regelverk	REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Contractual warranty	
Garanti	18 months