

Mer om SC420I

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



SC420I

APC Smart-UPS SC 420VA 230V

EAN: 0731304222613



 [Last ned produktdatablad for SC420I](#)

Karakteristikk

Overview

Presentasjon	APC Smart-UPS SC is ideal for small and medium businesses looking to protect networking equipment and point-of-sale (POS) devices from power disturbances and outages. The Smart-UPS SC features network grade protection, hot swap batteries, and built-in data line protection for worry free uninterruptible power protection for increased availability. Built on the same standards as the award-winning Smart-UPS, Smart-UPS SC provides the basic features and manageability needed to protect entry-level applications
Leveringstid	Usually in Stock

General

Inkludert utstyr	User manual Smart UPS signalling RS-232 cable CD with software
Product web sub-family	Entry level
Number of tare power	14 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	0U
Farge	Grå
Dybde	36,8 cm
Høyde	16,8 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	9,09 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	11,9 cm

Input

Network frequency	50/60 Hz +/- 3 Hz automatisk gjenkjenning
Plug standard	IEC 320 C14
Input voltage limits	195...265 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	260 W
Maximum configurable power in W	260 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	3 IEC 320 C13 1 IEC 320 C13 surge 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	420 VA
Merkeeffekt VA	420 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Produktsertifikater	CE EAC GOST NOM VDE VCCI
---------------------	---

Environmental

Omgivelsestemperatur drift	0..40 °C
Relativ fuktighet	0..95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage Relative Humidity	0..95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Varmeavgivelse	50 Btu/t

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	7,0 Ah

Battery charger power	28 W rated
Battery power in VAh	84 VAh runtime
Batterilevetid	3..5 år
Extended runtime	0
Communications & Management	
Ledige plasser	0
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rate	320 J
Noise suppression	Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ45 modem/fax/DSL/10-100 base-T protection
Packing Units	
Forpakning 1 vekt	10,23 kg
Forpakning 1 høyde	31,8 cm
Forpakning 1 bredde	26,2 cm
Forpakning 1 lengde	50,8 cm
Antall enheter forpakning 3	12
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
Contractual warranty	
Garanti	2 years repair or replace