

Mer om SC620I

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



SC620I

APC Smart-UPS SC 620VA 230V

EI-nummer: 6605351
EAN: 0731304222637



by Schneider Electric

 [Last ned produktdatablad for SC620I](#)



Karakteristikk

Overview

Presentasjon	APC Smart-UPS SC is ideal for small and medium businesses looking to protect networking equipment and point-of-sale (POS) devices from power disturbances and outages. The Smart-UPS SC features network grade protection, hot swap batteries, and built-in data line protection for worry free uninterruptible power protection for increased availability. Built on the same standards as the award-winning Smart-UPS, Smart-UPS SC provides the basic features and manageability needed to protect entry-level applications
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software Smart UPS signalling RS-232 cable User manual
Product web sub-family	Entry level
Number of tare power	15 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	0U
Farge	Grå
Dybde	37,5 cm
Høyde	16,8 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	12,27 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	11,9 cm

Input

Network frequency	50/60 Hz +/- 3 Hz automatisk gjenkjenning
Plug standard	IEC 320 C14
Input voltage limits	195...265 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	390 W
Maximum configurable power in W	390 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	3 IEC 320 C13 1 IEC 320 C13 surge 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	620 VA
Merkeeffekt VA	620 VA
Transfer time	2 ms typical

Conformance

Produktsertifikater	CE CE EAC GOST VDE VCCI
---------------------	--

Environmental

Omgivelsestemperatur drift	0..40 °C
Relativ fuktighet	0..95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage Relative Humidity	0..95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Varmeavgivelse	70 Btu/t

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	5 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	12,0 Ah
Battery charger power	26 W rated

Battery power in VAH	132 VAh runtime
Batterilevetid	3..5 år
Extended runtime	0
Communications & Management	
Ledige plasser	0
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rate	320 J
Noise suppression	Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ45 modem/fax/DSL/10-100 base-T protection
Packing Units	
Forpakning 1 vekt	13,18 kg
Forpakning 1 høyde	31,8 cm
Forpakning 1 bredde	26,2 cm
Forpakning 1 lengde	50,8 cm
Antall enheter forpakning 3	12
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
Contractual warranty	
Garanti	2 years repair or replace