

Mer om SMT1000I

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



SMT1000I

APC Smart-UPS 1000VA LCD 230V

EI-nummer: 6605325
EAN: 0731304268673



by Schneider Electric



 [Last ned produktdatablad for SMT1000I](#)

Karakteristikk

Oversikt

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 2 Weeks

General

Inkludert utstyr	CD with software Documentation CD Installation guide Smart UPS signalling RS-232 cable USB cable
Performance multiplier	1
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

Physical

Farge	Black
Dybde	43,9 cm
Høyde	21,9 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	18,86 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	17,1 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V adjustable 160...286 V
Inputvolt_other	220 V 240 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	700 W
Maximum configurable power in W	700 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Output voltage	220 V 240 V
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers
Curve equation	Efficiency
Curve fixed loss	0,0127
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0,0015
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Merkeeffekt VA	1000 VA

Conformance

Produktsertifikater	CE EAC RCM VDE
Standarder	ENIEC 62040-1 ENIEC 62040-2
Environmental	
Omgivelsestemperatur drift	0..40 °C
Relativ fuktighet	0..95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage Relative Humidity	0..95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	41 dBA
Varmeavgivelse	100 Btu/t
Show note OP temperature	No
Batteries & Runtime	
Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	Z
Battery charger power	88 W rated
Battery power in VAH	264 VAh runtime
Batterilevetid	3..5 år
Extended runtime	0
Communications & Management	
Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Optional
Surge Protection and Filtering	
Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Packing Units	
Forpakning 1 vekt	22,77 kg
Forpakning 1 høyde	37,6 cm

Forpakning 1 bredde	32,8 cm
Forpakning 1 lengde	59,5 cm
SCC14	731304268673
Antall enheter forpakning 3	12
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
Garantiperiode	
Garanti	3 years repair or replace (excluding battery) and 2 years for battery