

## Mer om SMX1500RMI2UNC

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-  
Electric tools

**SMX1500RMI2UNC**

APC Smart-UPS X 1500VA Rack/Tower LCD 230V with Network Card

EI-nummer: 6605332

EAN: 0731304281702



 [Last ned produktdatablad for SMX1500RMI2UNC](#)

## Karakteristikk

### Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 2 Weeks

### General

Product web sub-family	Network card pre-installed
Number of tare power	7 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### Physical

Kabellengde	1,83 m
Number of rack unit	2U
Farge	Black
Dybde	49 cm
Høyde	8,9 cm
Mounting preference	Lower
Vekt	24,82 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Bredde	43,2 cm

### Input

Brytekapasitet, A	10 A
Antall kabler	1

### Output

Merkeeffekt i W	1200 W
-----------------	--------

Maximum configurable power in W	1200 W
Harmonic distortion	Mindre enn 5 %
UPS type	Line interactive
Wave type	Sine wave
Maximum configurable power in VA	1500 VA
Merkeeffekt VA	1500 VA
<b>Conformance</b>	
Produktsertifikater	C-Tick CE VDE EAC
Standarder	EN 50091-1 EN 50091-2
<b>Environmental</b>	
Omgivelsestemperatur drift	0..45 °C
Relativ fuktighet	0..95 %
Driftshøyde	0..10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Varmeavgivelse	133 Btu/t
<b>Batteries &amp; Runtime</b>	
Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Liquid value	0
Batterilevetid	3..5 år
Extended runtime	0
<b>Communications &amp; Management</b>	
Ledige plasser	0
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes
<b>Surge Protection and Filtering</b>	
Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
<b>Packing Units</b>	

Forpakning 1 vekt	30 kg
Forpakning 1 høyde	24,6 cm
Forpakning 1 bredde	58,9 cm
Forpakning 1 lengde	62 cm
Antall enheter forpakning 3	8
<b>Offer Sustainability</b>	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	<a href="#">REACH-erklæring</a>
EU RoHS-direktiv	I samsvar <a href="#">EU RoHS-erklæring</a>
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	<a href="#">Ja</a>
Miljøinformasjon	<a href="#">Produktmiljøprofil</a>
Produktets livssyklus	<a href="#">Informasjon om levetidsslutt</a>
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
<b>Contractual warranty</b>	
Garanti	3 years repair or replace (excluding battery) and 2 years for battery