

Mer om SUA5000RMI5U

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



SUA5000RMI5U

APC Smart-UPS 5000VA 230V Rackmount/Tower

EI-nummer: 6605224

EAN: 0731304255321



by Schneider Electric



 Last ned produktdatablad for SUA5000RMI5U

Karakteristikk

Oversikt

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 4 Weeks

General

Inkludert utstyr	CD with software Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Smart UPS signalling RS-232 cable User manual Web/SNMP management card
Number of tare power	75 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	5U
Farge	Sort
Dybde	66 cm
Høyde	22,2 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	97,73 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	No
Bredde	48,3 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Number of input connectors	1 hard wire 3-wire
Input voltage limits	151...302 V adjustable 160...286 V
Forsyningsspenning	230 V
Output	
Merkeeffekt i W	4000 W
Maximum configurable power in W	4000 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 4 IEC Jumpers 2 IEC 320 C19
Effektivitet	96 % (fullastet)
Output voltage	230 V
Maximum configurable power in VA	5000 VA
Merkeeffekt VA	5000 VA
Transfer time	2 ms typical : 4 ms maximum
Conformance	
Produktsertifikater	C-Tick CE GOST VDE
Merking	GS Mark
Standarder	EN 50091-1 EN 50091-2
Environmental	
Omgivelsestemperatur drift	0..40 °C
Relativ fuktighet	0..95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage Relative Humidity	0..95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	53 dBA
Varmeavgivelse	430 Btu/t
Batteries & Runtime	
Batteritype	VRLA
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t

Number of battery replacement quantity	2
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery charger power	542 W rated
Battery power in VAH	1632 VAh runtime
Batterilevetid	3..5 år
Extended runtime	0
Communications & Management	
Ledige plasser	0
Preinstalled device	Network management card
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Audible and visible alarms : configurable delays
Surge Protection and Filtering	
Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Packing Units	
Forpakning 1 vekt	106,82 kg
Forpakning 1 høyde	63,5 cm
Forpakning 1 bredde	61 cm
Forpakning 1 lengde	76,2 cm
Antall enheter forpakning 2	1
Antall enheter forpakning 3	4
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
Garantiperiode	

Garanti

2 years repair or replace