



Teknisk informasjon

Serie	TeSys
Produkt eller type komponent	Kontaktor
Produktnavn	TeSys K
Kortnavn utstyr	LC1K
Applikasjon	Kontroll
Contactur application	Omsk last

Komplementær

Driftskategori	AC-1
Antall poler	4P
Power pole contact composition	2 NO + 2 NC
[Ue] merkespenning	Power circuit: 690 V AC 50/60 Hz
[Ie] nominell driftsstrøm	20 A (at $\leq 50\text{ }^\circ\text{C}$) at $\leq 440\text{ V AC AC-1}$ for power circuit 16 A (at $\leq 70\text{ }^\circ\text{C}$) at 690 V AC AC-1 for power circuit
Kontrollkretstype	AC at 50/60 Hz
Styrespenning	24 V AC 50/60 Hz
[Uimp] Nominell impuls spenning	8 kV
Overspenningskategori	III
[Ith] fri luft termisk strøm	20 A (at 50 °C) for power circuit
Irms rated making capacity	110 A AC for power circuit conforming to NF C 63-110 110 A AC for power circuit conforming to IEC 60947
Rated breaking capacity	110 A at 415 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 110 A at 220...230 V conforming to IEC 60947 110 A at 380...400 V conforming to IEC 60947 70 A at 660...690 V conforming to IEC 60947
[Icw] kort-tids/kortslutnings merkestrøm	90 A 50 °C - 1 s for power circuit 85 A 50 °C - 5 s for power circuit 80 A 50 °C - 10 s for power circuit 60 A 50 °C - 30 s for power circuit 45 A 50 °C - 1 min for power circuit 40 A 50 °C - 3 min for power circuit 20 A 50 °C - ≥ 15 min for power circuit
Sikringsstørrelse	25 A gG at $\leq 440\text{ V}$ for power circuit 25 A aM for power circuit
Gjennomsnittlig impedanse	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] isolasjonsspenning	Power circuit: 600 V conforming to UL 508 Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V conforming to CSA C22.2 No 14
Inrush power in VA	30 VA (at 20 °C)
Hold-in strømforbruk i VA	4.5 VA (at 20 °C)
Varmeavgivelse	1.3 W
Control circuit voltage limits	Operational: 0.8...1.15 U _c (at $\leq 50\text{ }^\circ\text{C}$) Drop-out: 0.2...0.75 U _c (at $\leq 50\text{ }^\circ\text{C}$)

Tilkoblingsklemmer	Screw clamp terminals 1 cable(s) 1.5...4 mm ² solid Screw clamp terminals 1 cable(s) 0.75...4 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.34...2.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 1.5...4 mm ² solid Screw clamp terminals 2 cable(s) 0.75...4 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.34...1.5 mm ² flexible with cable end
Bruksområde	3600 cyc/h
Signale krets frekvens	<= 400 Hz
Montering	Plate Skinne
Tiltrekningsmoment	1.3 N.M - on screw clamp terminals - with screwdriver Philips No 2 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
Driftstid	10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing 15...25 ms coil de-energisation and NC closing 5...15 ms coil energisation and NC opening
Sikkerhet pålitelighet nivå	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mekanisk levetid	10 Mcycles
Elektrisk levetid	0.18 Mcycles 20 A AC-1 at Ue <= 440 V
Mekanisk robusthet	Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations contactor closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6
Høyde	58 mm
Bredde	45 mm
Dybde	57 mm
Vekt	0,18 kg

Miljø

Standarder	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Produktsertifikater	CSA UL
IP-grad	IP2x conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068 TC conforming to DIN 50016
Omgivelsestemperatur for lagring	-50...80 °C
Operating altitude	2000 m without derating
Flammehemming	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	179,1 g
Forpakning 1 høyde	4,8 cm
Forpakning 1 bredde	6,2 cm
Forpakning 1 lengde	6,5 cm
Enhetstype forpakning 2	S02

Antall enheter forpakning 2	50
Forpakning 2 vekt	9,215 kg
Forpakning 2 høyde	15 cm
Forpakning 2 bredde	30 cm
Forpakning 2 lengde	40 cm

Offer Sustainability

REACH-regelverk	REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-Erklæring
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Contractual warranty

Garanti	18 months
---------	-----------