

Mer om VW3A46124

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**VW3A46124****Passiva filter 30A 400V 50Hz 5%THDi**

EI-nummer: 4177446

EAN: 3606480640155

 [Last ned produktdatablad for VW3A46124](#)

Karakteristikk**Teknisk informasjon**

Produkt eller type komponent	Passive filter
Produktspesifikk applikasjon	Reduction of current harmonics

Komplementær

Serie kompatibilitet	Altivar Process ATV900 Altivar Process ATV600 Altivar 71 Altivar 61
[Us] matespenning	400 V +/- 10 %
Power supply frequency	50 Hz +/- 2 %
Kv antum per stasjon	1 filter per drive for variable speed drive ATV61W motor: 15 kW/20 hp 1 filter per drive for variable speed drive ATV61H motor: 15 kW/20 hp 1 filter per drive for variable speed drive ATV71H motor: 15 kW/20 hp 1 filter per drive for variable speed drive ATV71W motor: 15 kW/20 hp 1 filter per drive for variable speed drive ATV650 veggmontering, motor: 15 kW/20 hp 1 filter per drive for variable speed drive ATV630 veggmontering, motor: 15 kW/20 hp 1 filter per drive for variable speed drive ATV950 veggmontering, motor: 15 kW/20 hp 1 filter per drive for variable speed drive ATV930 veggmontering, motor: 15 kW/20 hp
[In] merkestrøm	29 A for inngang 30 A for utgang
Antall faser i nettverket	3 faser
THDI	10 % for variable speed drive ATV61H motor: 15 kW/20 hp 10 % for variable speed drive ATV71H motor: 15 kW/20 hp 10 % for variable speed drive ATV71W motor: 15 kW/20 hp 5 % for variable speed drive ATV61W motor: 15 kW/20 hp 5 % for variable speed drive ATV650 motor: 15 kW/20 hp 5 % for variable speed drive ATV630 motor: 15 kW/20 hp 5 % for variable speed drive ATV950 motor: 15 kW/20 hp 5 % for variable speed drive ATV930 motor: 15 kW/20 hp
Max strøm	1.5 x nominal current (duration = 60 s)
Effektivitet	98 %

Varmetap	298 W
Cos phi	1 (150 % of line current) 0.85 (75 % of line current) 0.99 (100 % of line current)
Elektrisk tilkobling	X1-1...X2-3 klemme, tilkoblingskapasitet: 0.5 ... 10 mm ² A, B terminal, connection capacity: 2.5 mm ²
Elektrisk isolasjonsklasse	Klasse F
Vekt	34 kg
Miljø	
IP-grad	IP20 IP55 (enclosure mounting)
Vibrasjonsmotstand	2 mm peak to peak (f= 5...13.2 Hz) conforming to EN 60068-2-6 0.7 gn (f= 13.2...150 Hz) conforming to EN 60068-2-6
Relativ fuktighet	5..85 % without condensation
Omgivelsestemperatur for drift	45...60 °C (with current derating 3 % per °C) 5..45 °C (without current derating)
Omgivende lufttemperatur for oppbevaring	-25...55 °C storage in original packaging -25...65 °C during transport
Operating altitude	<= 1000 m uten strøm belastningsreduksjon > 1000...4000 m with current derating 5 % per 1000 m
Standarder	G5/4 engineering recommendation EN/IEC 61000-2-4 EN/IEC 61000-3-12 EN/IEC 61000-2-2 EN/IEC 61000-3-2 EN/IEC 61000-3-4
Packing Units	
Forpakning 1 vekt	34,000 kg
Forpakning 1 høyde	0,510 dm
Forpakning 1 bredde	0,400 dm
Forpakning 1 lengde	0,600 dm
Offer Sustainability	
REACH-regelverk	REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Garantiperiode	
Garanti	18 måneder