

ENSTO

Kortslutningsring, kaldkrymp

SCRKC2



Kode	SCRKC2
GTIN	6438100331146
El nummer	1103741
Navn	Kortslutningsring, kaldkrymp 0,6/1 (1,2) kV 1,5kA-1s Al 4x95 mm ²
Beskrivelse	Beskytter mot utilsiktet innkobling av kabel. Leveres med kaldkrymp endehette og mastik for å tette mot vann og skitt. Settet består av en aluminiumsring med skruer som tres over kabelen. Skruene skrues inn med skrumaskin med passende momentjustering. Testet etter fremgangsmåte i IEC61230. Begrenset opp imot kortslutningsverdier angitt i varetekst og datablad. For bruk på fire-leder aluminiums kabel.

Selger

Technical specification

Mål

Lengde:	70 mm
Leder tverrsnitt Al:	≥ 95 mm ²
Weight:	0,238 kg

Short-circuit characteristics

Nominell kortslutningsstrøm kort tid:	1,5 kA 1 s
---------------------------------------	------------

Others

ETIM Class:	EC000218
-------------	----------

ETIM Technical specification

etim

Type:	Cold-shrink
-------	-------------

Model:	Medium-walled
Shrink rate:	2:1
Inner diameter before heat-shrink:	45,5 mm
Inner diameter after heat-shrink:	84,3 mm
Total length after shrink:	115 mm
Nominal cross section:	$\geq 95 \text{ mm}^2$
Nominal diameter inch:	Other
Wall thickness after shrinking:	4 mm
Operation temperature:	$\geq 100 \text{ }^\circ\text{C}$
Colour:	Black
Material:	Ethylene-propylene diene rubber (EPDM)
Halogen free:	Yes
With inner glue:	No
Printable:	No
UL approval:	No

Packaging

Default package

Unit:	PCE
Package size:	5
Depth:	383 mm
Width:	258 mm
Height:	173 mm
Weight:	1,475 kg
Volume:	17,094822 l