

ENSTO

PRODUKTKORT

12.04.2022

Kortslutningsring, kaldkrymp

SCRKC4



Kode SCRKC4

GTIN 0498100331160

Details

Ei nummer 1103743

Navn Kortslutningsring, kaldkrymp

0,6/1 (1,2) kV 3,0kA-1s Al 4x240 mm²

We use cookies to ensure that we give you the best experience on our website. If you continue without changing your settings, we'll assume that you are happy to receive all cookies from this website. **Read more about our privacy policy** (<https://www.ensto.com/company/sustainability/policies-certificates/privacy-policy-for-website-users/>)

Beskrivelse Beskytter mot utilsiktet innkobling av kabel. Leveres med kaldkrymp endehette og mastik for å tette mot vann og skitt.

Settet består av en aluminiumsring med skruer som tres over kabelen. Skruene skrues inn med skrumaskin med passende momentjustering. Testet etter

Necessary

fremgangsmåte i IEC61230. Begrenset opp imot kortslutningsverdier angitt i varetekst og datablad. For bruk på fire-leder aluminiums kabel.

Preferences
Selger

Statistics

Technical specification

Marketing

Mål

Lengde:	70 mm	
Leder tverrsnitt Al:	≥ 240 mm ²	OK
Weight:	0,27 kg	

Short-circuit characteristics

Powered by **Cookiebot by Usercentrics** (<https://www.cookiebot.com/>)

Nominell kortslutningsstrøm kort tid: 3,0 kA 1 s

Others

ETIM Class: EC000218

ETIM Technical specification

etim

Type: Cold-shrink

Model:	Medium-walled
Shrink rate:	2:1
Inner diameter before heat-shrink:	45,5 mm
Inner diameter after heat-shrink:	84,3 mm
Total length after shrink:	115 mm
Nominal cross section:	≥ 240 mm ²
Nominal diameter inch:	Other
Wall thickness after shrinking:	4 mm
Operation temperature:	≥ 100 °C
Colour:	Black
Material:	Ethylene-propylene diene rubber (EPDM) (https://www.cookiebot.com/)

Halogen free:	Yes	Consent	Details	About
With inner glue:	No			

Printable: No

About cookies

No

We use cookies to ensure that we give you the best experience on our website. If you continue without changing your settings, we'll assume that you are happy to receive all cookies from this website. **Read more about our privacy**

policy (<https://www.ensto.com/company/sustainability/policies-certificates/privacy-policy-for-website-users/>)

Default package

Unit:	PCE
Package size:	5
Depth:	383 mm
Width:	258 mm
Height:	173 mm
Weight:	1,592 kg
Volume:	17,094822 l

Preferences

Statistics

Marketing

OK

Powered by **Cookiebot by Usercentrics** (<https://www.cookiebot.com/>)