



Adhesive-lined heat shrinkable end cap which enables easy protection and sealing of cables terminations from environmental effects.

FEATURES AND BENEFITS

- UV stabilized
- Good chemical and solvent resistance
- Thermoplastic liner provides complete environmental seal
- Shrink ratio: >2:1
- Continuous operating temperature: -40°C to 100°C
- Shrink temperature: 125°C min.

STANDARDS

- IEC 62677
- ESI 09-11

TYPICAL APPLICATIONS

- Sealing of cables against moisture
- Rated to 1000V for stop ends under load



>2:1
SHRINK RATIO

-40°C to 100°C
(-40°F to 212°F)
CONTINUOUS OPERATING
TEMPERATURE

MARKETS:

Renewables, Industrial, Power
Distribution, Utility

STANDARDS:



Crosslinked polyolefin end cap

DIMENSIONS

ORDER NUMBER	EXPANDED		RECOVERED								DELIVERY UNITS
	Internal Diameter (min) D		Internal Diameter (max) d		Total Wall Thickness (nom) W		Length (min)		Recommended Diameter Range		Pieces
	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	
CEC 10/4	10.0	0.394	4.0	0.157	2.00	0.079	35	1.378	4.5-8.0	0.18-0.31	200
CEC 15/4.5	15.0	0.591	4.5	0.177	2.00	0.079	45	1.772	5.0-12.0	0.20-0.47	150
CEC 20/6	20.0	0.787	6.0	0.236	2.70	0.106	60	2.362	7.0-17.5	0.28-0.69	150
CEC 25/9	25.0	0.984	9.0	0.354	2.70	0.106	70	2.756	10.0-22.0	0.39-0.87	100
CEC 36/15	36.0	1.417	15.0	0.591	2.80	0.110	95	3.740	17.0-30.0	0.67-1.18	100
CEC 63/24	63.0	2.480	24.0	0.945	3.60	0.142	110	4.331	28.0-55.0	1.10-2.17	50
CEC 80/40	80.0	3.150	40.0	1.575	3.60	0.142	130	5.118	45.0-70.0	1.77-2.76	30
CEC 102/60	102.0	4.016	60.0	2.362	3.60	0.142	152	5.984	68.0-90.0	2.68-3.54	20
CEC 124/60	124.0	4.882	60.0	2.362	3.60	0.142	152	5.984	75.0-110.0	2.95-4.33	20
CEC 148/57	148.0	5.827	57.0	2.244	4.50	0.177	152	5.984	80.0-135.0	3.15-5.31	10



ORDERING

Select a dimension which will shrink snugly over the application to be covered. If recovery is restricted the resultant wall thickness will be less than specified.

- Select options:
 - Color: Black (BK)
- Please specify the product name, order number and options you require
- *Example:* CEC 36/15, black, 1,000 pcs

Please contact your Customer Service Representative for information on custom colors, sizes, lengths and material data sheet.