

**Rubber Mastic (RM) Tapes**

A self-bonding mastic tape consisting of an ethylene propylene rubber (EPR) backing, bonded to a tacky, temperature stable, electrical grade mastic. Use for insulating and moisture sealing splices and terminations on solid dielectric cable. Can be wrapped, stretched or molded around irregular shapes for insulation build-up, water-sealing, and surface protection. Provides excellent electrical properties, superior adhesion, moisture and chemical resistance. For primary insulation up to 2kV.

**Vinyl Mastic (VM) Tapes**

A self-fusing mastic compound with an all-weather, premium vinyl backing that can be used for insulating and water-sealing electrical connections through 600 volts. Small roll sizes can be stretched and molded around irregular shapes, even in tight locations. Provides excellent electrical properties, superior adhesion, and moisture and chemical resistance. Vinyl backing adds UV protection. Use for insulating overhead and direct buried low voltage connections, motor lead connections, and cable and conduit repair.

**INSULATING MASTICS**



**RUBBER MASTIC (RM) Tapes**

Cat.	Form	Dimensions		Packaging	Weight
2619	roll	1 1/2" x .065" x 10'	38mm x 1,65mm x 3m	30/case IB	19 lbs 9 kg
2625	roll	2" x .065" x 10'	50mm x 1,65mm x 3m	30/case B	30 lbs 14 kg
2719	roll	1" x .065" x 10'	25mm x 1,65mm x 3m	10box/100case	44 lbs 20 kg

**VINYL MASTIC (VM) Tapes**

Cat.	Form	Dimensions		Packaging	Weight
2617	roll	3/4" x .025" x 20'	25mm x 0,635mm x 6m	80/case IB	30 lbs 14 kg
2618	roll	1 1/2" x .025" x 20'	44mm x 0,635mm x 6m	40/case IB	30 lbs 14 kg
2609	roll	4" x .050" x 10'	100mm x 1,3mm x 3m	10/case IB	13 lbs 6 kg