




Product data sheet

Item No. 57.570.0155.0

Feed-through terminal WKN 70 / U /V0

Feed-through DIN rail terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 70 mm<sup>2</sup>, width 24 m m, color gray



Item No.	57.570.0155.0
EAN	4015573506855
Order Unit	20 Piece(s)

Certificates / Approvals



## Technical data

Nominal cross section	70 mm <sup>2</sup>	
Colour	Grey	
Number of levels	1	
Number of clamp positions per level	2	
Width/grid dimension	24 mm	
Insulating housing	PA666	
Inflammability class of insulation material acc. with UL94	VO	
Explosion-tested version "Ex e"	Yes	
Mounting method	DIN rail (top hat rail)/G-rail	
Terminal blocks for electrical installations	No	
Technical data		
Rated current	179 A	
Rated voltage	800 V	
Rated impulse voltage	8 kV	
Pollution degree	3	
Closing plate required	No	
Type of insulation material	Thermoplastic	
Length	76.8 mm	
Connection Data		
Connection type 1	Screw connection	
Connection type 2	Screw connection	

10 mm<sup>2</sup>

Minimum cross section fine stranded





Maximum cross section fine stranded	70 mm²
Minimum cross section stranded	16 mm²
Maximum cross section stranded	95 mm²
Wire strip length	24 mm
Torque conductor mounting	6 Nm

## Technical Data UL/CSA

Cross section UL	6-2/0 AWG
Voltage UL	600 V
Current factory wiring	175 A
Current field wiring	175 A
Cross section CSA	6-2/0 AWG
Voltage CSA	600 V
Current CSA	170 A

## Technical drawing

