

Product data sheet

Item No. 92.031.5153.1

Female connector GST18I3I B1V F5 1 SW

Flat cable adapter GST18i3, 250 V, 16 A, for tapping off the phase L1, N and PE of the flat cable mains 5 x 2,5 mm², output with female connector, at right angles to cable entry



Item No.	92.031.5153.1
EAN	4015573642539
Order Unit	50 Piece(s)

Certificates / Approvals

Technical data

General

Rated voltage	250 V
Rated current	16 A
Degree of protection (IP)	IP20
Mechanical coding	Yes
Marking of poles	L, N, PE
Color of coding/ contact carrier	Black
Colour housing	Black-transparent
Lockable	Yes

Model

Model	Tapp-off
Number of poles	3
Selection of phase	L1

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C



Dimensions

Length	57.5 mm
Width	34.5 mm
Height	25 mm

Technical drawing

Abdeckung cover
Polycarbonat, transparent
lose beigelegt
polycarbonate, transparent
unassembled

Grundplatte base plate
PA 66 halogenfrei, schwarz
lose beigelegt
PA 66 halogen-free, black
unassembled

Buchse teil female connector
PA 66 halogenfrei,
PA 66 halogen-free
Farbe: siehe Tabelle
color: see table

Teile - Nr. part number	Typ type	Anschluß connection	Farbe color
92.031.5153.1	GST18131 B1V F5 1	L1;N;PE	schwarz/black
92.031.5253.1	GST18131 B1V F5 2	L2;N;PE	schwarz/black
92.031.5353.1	GST18131 B1V F5 3	L3;N;PE	schwarz/black

Weitere Daten siehe Katalog
further data see catalog

Female Connector Vertical
BUCHSENTEIL_VERTICAL
für Flachbandkabel/for flat cable
5x2,5mm