

Product data sheet

Item No. 92.232.1000.2

Cable assembly GST18I3K1BS 15E 10WS

geis® Extension cable female - male; length: 1m; type GST18I3;  
3-pole; 250 V / 16 A; colour of coding: white with white strain-relief;  
cable: H0 5VV-F 3G1,5, colour: white, fire class Eca



Item No.	92.232.1000.2
EAN	4015573324619
Order Unit	75 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

Model

Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	White
Cable diameter	8.3 mm
Version of cable	Female - male
Type of cord set	Connecting cable



Version cable end 1	GST18i3 female
Version cable end 2	GST18i3 plug

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

**Dimensions**

Total length	1 m
--------------	-----

**Technical drawing**

Buchsteil/female connector      Steckerteil/male connector

Kabel/cable H05VV-F3G1,5  
Farbe/colour: siehe Tabelle/see table

Gesamtlänge / total length L ± 3%

.F	Farbe colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour
.1	schwarz black	N ⊕ L	L ⊕ N	schwarz black
.2	weiß white	N ⊕ L	L ⊕ N	weiß white
.3	grau grey	N ⊕ L	L ⊕ N	schwarz black
.5	rot red	N ⊕ L	L ⊕ N	schwarz black

SW = schwarz/black  
WS = weiß/white  
GR01 = grau/grey  
RT03 = rot/red

Typ/type: GST1813K1BS 15

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX00.F	XX in dm-Schritten	92.232.1000.1 = 10dm/L= 1000mm	GST1813K1BS 15 10SW
U2.232.XX00.F	XX in m-Schritten	U2.232.1200.1 = 12 m/L=12000mm	GST1813K1BS 15 X12SW
92.232.XX90.F	XX in dm-Schritten	92.232.1090.1 = 10dm/L= 1000mm	

90.F = spezielle Verpackung und Etikettierung nach A 1960.000  
special packaging and lable according to A 1960.000

Unterlegungsgröße ISO 14224/Envelope system Size ISO 14224  
This ISO-standard describes the envelope principle. According to the envelope principle the dimensions of formed parts (e.g. pins) are limited by the size tolerances.  
Größenangaben sind in mm angegeben.  
Dimensions are given in mm.

Zeichnung Nr./Drawing No. 92.232.0200.1 01K a

PRE-ASSEMBLED CABLE KONFEKT LEITUNG  
Buchse/female - Stecker/male 1.5mm  
Crimpsführung/crimpression K1 250V

weitere Daten siehe Katalog  
further data see catalog