

Product data sheet

Item No. 92.232.6000.2

Cable assembly GST18I3K1BS 15E 60WS

geis® Extension cable female - male; length: 6m; type GST18I3;  
3-pole; 250 V / 16 A; colour of coding: white with white strain-relief;  
cable: H0 5VV-F 3G1,5, colour: white, fire class Eca



Item No.	92.232.6000.2
EAN	4015573369313
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

Model

Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	White
Cable diameter	8.3 mm
Version of cable	Female - male
Type of cord set	Connecting cable



Version cable end 1	GST18i3 female
Version cable end 2	GST18i3 plug

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

**Dimensions**

Total length	6 m
--------------	-----

**Technical drawing**

Buchsteil/female connector      Steckerteil/male connector

Kabel/cable H05VV-F3G1,5  
Farbe/colour: siehe Tabelle/see table

Gesamtlänge / total length L ± 3%

.F	Farbe colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour
.1	schwarz black	N ⊕ L	L ⊕ N	schwarz black
.2	weiß white	N ⊕ L	L ⊕ N	weiß white
.3	grau grey	N ⊕ L	L ⊕ N	schwarz black
.5	rot red	N ⊕ L	L ⊕ N	schwarz black

Typ/type: GST1813K1BS 15 .. SW = schwarz/black  
WS = weiß/white  
GR01 = grau/grey  
RT03 = rot/red

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX00.F	XX in dm-Schritten	92.232.1000.1 = 10dm/L= 1000mm	GST1813K1BS 15 10SW
U2.232.XX00.F	XX in m-Schritten	U2.232.1200.1 = 12 m/L=12000mm	GST1813K1BS 15 X12SW
92.232.XX90.F	XX in dm-Schritten	92.232.1090.1 = 10dm/L= 1000mm	

90,F = spezielle Verpackung und Etikettierung nach A 1960.000  
special packaging and table according to A 1960.000

Unterlegungsgröße ISO 14224/Envelope system size ISO 14224  
This ISO-standard describes the envelope principle. According to the envelope principle the dimensions of formed parts (e.g. pins) are limited by the size tolerances.  
Größenangaben in mm/Dimensions in mm

Zeichnung Nr./Drawing No. 92.232.0200.1 01K a

PRE-ASSEMBLED CABLE KONFEKT LEITUNG  
Buchse/female - Stecker/male 1.5mm  
Crimpsführung/crimpsplicing K1 250V

Wieland logo

00-FEB-08/916