

Product data sheet
Item No. 92.238.1000.2
Cable assembly GST18I3K1BS 25E 10WS

 gesis® Extension cable female - male; length: 1m; type GST18I3;
 3-pole; 250 V / 20 A; colour of coding: white with white strain-relief;
 cable: H0 5VV-F 3G2,5, colour: white, fire class Eca


| | |
|------------|---------------|
| Item No. | 92.238.1000.2 |
| EAN | 4015573356641 |
| Order Unit | 50 Piece(s) |

Certificates / Approvals

Technical data
General

| | |
|--|----------|
| Rated current | 20 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 1 |
| Lockable | Yes |
| Color of coding/ contact carrier | White |
| Marking of poles | L, N, PE |
| Color of housing inclusive strain relief | White |

Model

| | |
|---------------------------------|---------------------|
| Nominal cross section conductor | 2.5 mm ² |
| Degree of protection (IP) | IP20 |
| Cable type | H05VV-F |
| Cable colour | White |
| Cable diameter | 10.2 mm |
| Version of cable | Female - male |
| Type of cord set | Connecting cable |



| | |
|---------------------|----------------|
| Version cable end 1 | GST18i3 female |
| Version cable end 2 | GST18i3 plug |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | No |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |
| Fire class | Eca |

Dimensions

| | |
|--------------|-----|
| Total length | 1 m |
|--------------|-----|

Technical drawing

Buchsteil/female connector Steckersteil/male connector

Gesamtlänge / total length

Kabel/cable: H05VV-F3G2,5
Farbe/colour: siehe Tabelle/see table

| Farbe colour | Codierung Buchse female | Codierung Stecker male | Kabelfarbe cable colour |
|------------------|-------------------------|------------------------|-------------------------|
| .1 schwarz black | N R L | L R N | schwarz black |
| .2 weiß white | N R L | L R N | weiß white |
| .3 grau grey | N R L | L R N | schwarz black |
| .5 rot red | N R L | L R N | schwarz black |

| Teile-Nr. part-no. | L | Beispiel (Farbe: schwarz) example (colour: black) | Typ type |
|--------------------|--------------------|---|----------------------|
| 92.238.XX00.F | XX in dm-Schritten | 92.238.1000.1 = 10dm/L= 1000mm | GST18i3K1BS 25 10SW |
| U2.238.XX00.F | XX in m-Schritten | U2.238.1200.1 = 12 m/L=12000mm | GST18i3K1BS 25 X12SW |

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Typ/type: GST18i3K1BS 25

Further data see catalog / further data see catalog

PRE-ASSEMBLED CABLE KONFEKT-LEITUNG
Buchse/female-Stecker/male Crimpversion K1
250V AC 20A 2,5mm