

Product data sheet

Item No. 92.238.1004.1

Cable assembly GST18I3K1-S 25E 10SW

geis® Connection cable male - free end; length: 1m; type GST18I3; 3-pole; 250 V / 20 A; colour of coding: black with black strain-relief; cable : H05VV-F 3G2,5, colour: black, fire class Eca



Item No.	92.238.1004.1
EAN	4015573356672
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black



Cable diameter	10.2 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	1 m
--------------	-----

Technical drawing

Kabel/cable H05VV-F362,5
Farbe/colour: siehe Tabelle/see table

.F	Farbe colour	Codierung *X* Stecker make	Kabelfarbe cable colour
.1	schwarz black	L R N	schwarz black
.2	weiß white	L R N	weiß white
.3	grau grey	L R N	schwarz black
.5	rot red	L R N	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) exampel (colour: black)	Typ type
92.238.XX04.F	XX in dm-Schritten	92.238.1004.1 = 10dm/L = 1000mm	GST18i3K1-S 25 10SW
U2.238.XX04.F	XX in m-Schritten	U2.238.1204.1 = 12 m/L = 12000mm	GST18i3K1-S 25 X12SW

Typ/type: GST18i3K1-S 25 .. SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Freiwillig nach /	ISO	Zusatz: keine weiteren Änderungen /	Änderung /	Bezeichnung / Drawing No.	92.238.0204.1 01K	Index
Material /	Werkstoff/Material	2106	Stecker /	Stecker I.		
Material /	Material	01.02	Stecker I.			
Vol. /	Vol.	011/011	Stecker I.			
Änderung/Revision	Änderung/Revision					

PRE-ASSEMBLED CABLE
KONFEKT LEITUNG
Stecker/male: freies Ende/free end Impression KI
© 250V AC 20A 2,5mm

001-FEB-18/916