

Product data sheet

Item No. 92.238.3000.1

Cable assembly GST18I3K1BS 25E 30SW

geis® Extension cable female - male; length: 3m; type GST18I3;
3-pole; 250 V / 20 A; colour of coding: black with black strain-relief;
cable: H0 5VV-F 3G2,5, colour: black, fire class Eca



Item No.	92.238.3000.1
EAN	4015573359239
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Female - male
Type of cord set	Connecting cable



Version cable end 1	GST18i3 female
Version cable end 2	GST18i3 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	3 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour
.1	schwarz black	N R L	L R N	schwarz black
.2	weiß white	N R L	L R N	weiß white
.3	grau grey	N R L	L R N	schwarz black
.5	rot red	N R L	L R N	schwarz black

Kabel/cable: H05VV-F3G2,5
Farbe/colour: siehe Tabelle/see table

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX00.F	XX in dm-Schritten	92.238.1000.1 = 10dm/L= 1000mm	GST18i3K1BS 25 10SW
U2.238.XX00.F	XX in m-Schritten	U2.238.1200.1 = 12 m/L=12000mm	GST18i3K1BS 25 X12SW

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Typ/type: GST18i3K1BS 25

Weitere Daten siehe Katalog
further data see catalog

Übersetzung Size 150 IEC/EN/Terrance system Size 150 IEC/EN. This ISO-standard describes the envelope principle. According to the envelope principle the deviation of formed parts (tolerance) are limited by the size tolerances. Zeichnung und Detailzeichnung nach DIN EN ISO 10110-01 (1st edition). Contents will be replaced by the document 00-104-0101 (1st of prohibited / derivate materials substances) to be decided.

Preferential next Serial tolerance: 30 - Zeichnung, keine erweiternde Änderungen / drawing, no normal modifications allowed. 1 - Fertigung First use. Zeichnung Nr./Drawing No. 92.238.0200.1 01K a

Material: Buchst./Material: 2006: Tag/Date: Name: T

Wieland logo and PRE-ASSEMBLED CABLE KONFEKT LEITUNG Buchse/female-Stecker/male Crimpversion K1 250V AC 20A 2,5mm