

Product data sheet

Item No. 92.238.7000.1

Cable assembly GST18I3K1BS 25E 70SW

geis® Extension cable female - male; length: 7m; type GST18I3;
3-pole; 250 V / 20 A; colour of coding: black with black strain-relief;
cable: H0 5VV-F 3G2,5, colour: black, fire class Eca



Item No.	92.238.7000.1
EAN	4015573370586
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Female - male
Type of cord set	Connecting cable



Version cable end 1	GST18i3 female
Version cable end 2	GST18i3 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	7 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour
.1	schwarz black	N R L	L R N	schwarz black
.2	weiß white	N R L	L R N	weiß white
.3	grau grey	N R L	L R N	schwarz black
.5	rot red	N R L	L R N	schwarz black

Kabel/cable: H05VV-F3G2,5
Farbe/colour: siehe Tabelle/see table

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX00.F	XX in dm-Schritten	92.238.1000.1 = 10dm/L= 1000mm	GST18i3K1BS 25 10SW
U2.238.XX00.F	XX in m-Schritten	U2.238.1200.1 = 12 m/L=12000mm	GST18i3K1BS 25 X12SW

Typ/type: GST18i3K1BS 25 ..
SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Weitere Daten siehe Katalog
further data see catalog

Unterliegend Size 150 IEC/EN, Technische system Size 150 IEC/EN, This ISO-standard describes the envelope principle. According to the envelope principle the deviation of formed parts from the size tolerances, in particular the deviation of formed parts from the size tolerances, are limited by the size tolerances.

Präferenzmaßmaßstab: DIN - Zeichnung, siehe entsprechende Abstände / First use: DIN - drawing, see corresponding distances

Zeichnung Nr./Drawing No. 92.238.0200.1 01K a

PRE-ASSEMBLED CABLE KONFEKT LEITUNG

Buchse/female-Stecker/male Crimpversion K1 250V AC 20A 2,5mm

00-FER-08/916