

Product data sheet

Item No. 92.238.8000.1

Cable assembly GST18I3K1BS 25E 80SW

geis® Extension cable female - male; length: 8m; type GST18I3;  
3-pole; 250 V / 20 A; colour of coding: black with black strain-relief;  
cable: H0 5VV-F 3G2,5, colour: black, fire class Eca



Item No.	92.238.8000.1
EAN	4015573370609
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	2.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Female - male
Type of cord set	Connecting cable



Version cable end 1	GST18i3 female
Version cable end 2	GST18i3 plug

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

**Dimensions**

Total length	8 m
--------------	-----

**Technical drawing**

Buchsteil/female connector      Steckersteil/male connector

Gesamtlänge / total length

Kabel/cable: H05VV-F3G2,5  
Farbe/colour: siehe Tabelle/see table

Farbe colour	Codierung Buchse female	Codierung Stecker male	Kabelfarbe cable colour
.1 schwarz black	N R L	L R N	schwarz black
.2 weiß white	N R L	L R N	weiß white
.3 grau grey	N R L	L R N	schwarz black
.5 rot red	N R L	L R N	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX00.F	XX in dm-Schritten	92.238.1000.1 = 10dm/L= 1000mm	GST18i3K1BS 25 10SW
U2.238.XX00.F	XX in m-Schritten	U2.238.1200.1 = 12 m/L=12000mm	GST18i3K1BS 25 X12SW

SW = schwarz/black  
WS = weiß/white  
GR01 = grau/grey  
RT03 = rot/red

Typ/type: GST18i3K1BS 25

Further data see catalog / further data see catalog

PRE-ASSEMBLED CABLE KONFEKT-LEITUNG  
Buchse/female-Stecker/male Crimpversion K1  
250V AC 20A 2,5mm