

Product data sheet

Item No. 92.257.2000.1

Cable assembly GST18I5KSBS 15E 20SW

geis® Extension cable female - male; length: 2m; type GST18I5;  
5-pole; 2 50/400 V / 16 A; colour of coding: black with black strain-  
relief; cable : H05VV-F 5G1,5, colour: black, fire class Eca



Item No.	92.257.2000.1
EAN	4015573587915
Order Unit	20 Piece(s)

**Certificates / Approvals**

**Technical data**
**General**

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	3, N, PE, 2, 1
Color of housing inclusive strain relief	Black

**Model**

Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Female - male
Type of cord set	Connecting cable
Version cable end 1	GST18i5 female
Version cable end 2	GST18i5 plug

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

**Dimensions**

Total length	2 m
--------------	-----



Technical drawing

Buchenteil/female connector      Steckerteil/male connector

Kabel/cable H05VV-F 5G1,5  
Farbe/colour: siehe Tabelle/see table

76,4      76,4      47,9      12,6 ± 0,15

Gesamtlänge / total length L ± 3%

Typ/type: GST1815KSBS 15      SW = schwarz/black  
WS = weiß/white

.F	Farbe colour	Codierung •X• Buchse female	Codierung •Y• Stecker male	Kabelfarbe cable colour
.1	schwarz black	3 N PE 2 1	1 2 PE N 3	schwarz black
.2	weiß white			weiß white

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Type
92.257.XX00.F	XX in dm-Schritten	92.257.1000.1 = 10dm/L= 1000mm	GST1815KSBS 15 10SW
U2.257.XX00.F	XX in m-Schritten	U2.257.1200.1 = 12 m/L=12000mm	GST1815KSBS 15 X12SW

Further information: [www.wieland.com](http://www.wieland.com)

Further data see catalog  
further data see catalog

Wieland  
Waldschla  
Vertriebskompan

PRE-ASSEMBLED CABLE  
KONFEKTLEITUNG

Buchse/female - Stecker/male  
Schraubanschluss/screw connection 250/400V 1,5gmm