

Product data sheet

Item No. 92.257.6000.1

Cable assembly GST18I5KSBS 15E 60SW

geis® Extension cable female - male; length: 6m; type GST18I5;
5-pole; 2 50/400 V / 16 A; colour of coding: black with black strain-
relief; cable : H05VV-F 5G1,5, colour: black, fire class Eca



Item No.	92.257.6000.1
EAN	4015573587953
Order Unit	8 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	3, N, PE, 2, 1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Female - male
Type of cord set	Connecting cable
Version cable end 1	GST18i5 female
Version cable end 2	GST18i5 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	6 m
--------------	-----



Technical drawing

Buchenteil/female connector Steckerteil/male connector

Kabel/cable H05VV-F 5G1,5
Farbe/colour: siehe Tabelle/see table

76,4 76,4 47,9 12,6 ± 0,15

Gesamtlänge / total length L ± 3%

Typ/type: GST1815KSBS 15 SW = schwarz/black
WS = weiß/white

.F	Farbe colour	Codierung •X• Buchse female	Codierung •Y• Stecker male	Kabelfarbe cable colour
.1	schwarz black	3 N PE 2 1	1 2 PE N 3	schwarz black
.2	weiß white			weiß white

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Type
92.257.XX00.F	XX in dm-Schritten	92.257.1000.1 = 10dm/L= 1000mm	GST1815KSBS 15 10SW
U2.257.XX00.F	XX in m-Schritten	U2.257.1200.1 = 12 m/L=12000mm	GST1815KSBS 15 X12SW

Further information: www.wieland-electric.com

Further data see catalog
weiterer Daten siehe Katalog

Wieland
Wielandische
Verbindungen

PRE-ASSEMBLED CABLE
KONFEKTLEITUNG

Buchse/female - Stecker/male
Schraubanschluss/screw connection 250/400V 1,5gmm