

Product data sheet

Item No. 94.425.4033.9

Cable assembly BST14I2KFB- 50L 40PB02

geis® Connection cable female - free end; length: 4m; type BST14I2; 2-pole; 50 V / 3 A; colour of coding: pastel blue with black strain-relief; cable: L03VV-U 2X0,5, colour: black



Item No.	94.425.4033.9
EAN	4015573802933
Order Unit	30 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	3 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	2
Mechanical coding	Yes
Lockable	No
Color of coding/ contact carrier	Pastel blue
Marking of poles	1+, 2-
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	0.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	21 mm
Preparation of conductor ends	Other
Cable type	L03VV-U
Cable colour	Black
Cable diameter	4.8 mm
Version of cable	Female - free end



Type of cord set	Connection cable
Version cable end 1	female
Version cable end 2	Free end

Material

Surface finish	Gilt
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Isoliergehäuse schwarz
insulating housing black

Buchseinsatz pastellblau
socket insert pastel blue

14,4 12,9 1,6 4,7 15,2

ⓐ Gesamtlänge/total length = (L+50) + 3% (L < 3000mm)
Gesamtlänge/total length = (L+100) + 3% (L > 3000mm)

Weitere Daten siehe Katalog
further data see catalog

Teilenummer part number	L	Beispiel example	Typ type
94.425.XX33.9	XX in dm-Schritten XX in dm-steps	94.425.1033.9 = 10dm /L= 1000mm	BST1412KFB- 50L 10PB02
U4.425.XX33.9	XX in m-Schritten XX in m-steps	U4.425.1233.9 = 12 m /L=12000mm	BST1412KFB- 50L X12PB02

2 Pole/2 poles

Pol pole	Aderfarbe conductor colour
+	rot/red
-	schwarz/black

Material	2007	Tag/Batch	Name	Zeichnung Nr./Drawing No.	Index
Material	27.04.	Schnitt	T	94.425.1033.9 01K	a
Material	201.	Erst-/First Use	Erst-/First Use		
wieland		Type		Bezeichnung/Title	
Mikroflex Vieladringspan		KONFEKT-LEITUNG		Niedervolt 50V - 3A 0,5 gmm BU/- connection cable female-free end	
Änderung/Revision		00-FEB-08/916			