

Product data sheet
Item No. 96.232.1000.1
Cable assembly RST20I3K1BS 15P 10SW

RST 20i3/2 extension cable female - male, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H05VV-F, length 1.0m, cross section 1.5mm², coding-color black



Item No.	96.232.1000.1
EAN	4015573761087
Order Unit	75 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm



Version of cable	Female - male
Type of cord set	Extension cable
Version cable end 1	female
Version cable end 2	male
Screened	No

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----

Technical drawing

	.F Farbe colour	Codierung Buchse female	Codierung Stecker male	Verriegelung locking
	.0 lichtgrau light grey	N PE	PE N	05.583.2953 schwarz / black
	.1 schwarz black	L	L	05.583.2954 schwarz / black

Weitere Daten siehe Katalog
further data see catalog

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
96.232.XX00.F	XX in dm-Schritten	96.232.1000.1 = 10dm/L= 1000mm	RST2013K1BS 15P 10SW
U6.232.XX00.F	XX in m-Schritten	U6.232.1200.1 = 12 m/L=12000mm	RST2013K1BS 15P X12SW

Typ/type: RST2013K1BS 15P .. GL = lichtgrau/light grey
SW = schwarz/black

Fertigung nach DIN 7165/Platenbau system acc. to DIN 7167. This DIN standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.		Zeichn. 02 Zeichnungs- und Dokumentationscode nach DIN EN 60918 ist verwendet. Conformity with Wieland document 02-10M-05/10 (list of prohibited / disallowed features subjected to be detected)	
Präzisions nach General tolerance	00 - Feinung, keine maximale Fertigung 01 - Feinung, maximale Fertigung	1 - Strömung First Use	Blatt: 1 von 1 sheet: 1 of 1
Werkstoff/Material		2005 Material 24.10 Parameter K	Zeichnung Nr./Drawing No. 96.232.0400.0 01K
16.02.2007 21.02.2007 23.02.2007 08/07/2007 08/07/2007		Zeichn. für/Replacement for: - Type pre-assembled cable KONFEKT LEITUNG Install. assembly / Test lead system Buchse/Stecker / male/female Crimping / crimp design 01.2509.16A	