



Product data sheet

Item No. 96.232.4004.0

Cable assembly RST20l3K1-S 15P 40GL

RST 20i3/2 connection cable male - free end, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H05VV-F, length 4.0m, cross section 1.5mm², coding-color light grey



Item No.	96.232.4004.0
EAN	4015573761438
Order Unit	25 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends





Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	Free end
Version cable end 2	male
Screened	No

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continous temperature	100 °C

Dimensions

Total length 4 m	m I
------------------	-----

Technical drawing

