



HF-COILFIX

Xpress and with pulling wire

PRODUCT HF-COILFIX Xpress empty pipe

APPLICATION

For open and hidden installation in walls, sealing and deck. May be embedded in concrete.

CONSTRUCTION EN 61386-1, EN 61386-22

Material Polypropylen, corrugated, flexible, fire resistand and selfextinguishing

Marking Production date, meter marking

Outer sheet Corrugated in color RAL 7035

Fire performance EN 61034-2, EN 50267-2-1/2, EN 61386-1/21/22

Packaging Coilfix 50m: - D: 420m, H 230mm - 100m: - D:400mm, H 300mm
25mm 50m: D 480, H250

ELECTRICAL SPECIFICATION

Insulation resistance >100MΩ ved 500V i 1 minut

Test EN 50267-2-1, EN 50267-1-2

Electrical test >2,0kV 50Hz in 15 minutes

APPLICATION SPECIFICATION

Mechanical force 750N

Temperature installation -5 - + 90° C

Temperature operation -25 - + 90° C

MARKING / APPROVALS / DIRECTIVES

ROHS 2011/65

Low Voltage Directive L.V.D. 2014/35/EU



 House	 Indoor	 Halogenfree	 Innmuret Gulv	 Selvslukken de IEC60332-1	 RoHS	 Etsende gasser	 Reach	 Omgivelses temp	 Lav røyk-utvikling	 Boyeradius	 Mekanisk motstandsdyktighet
--	---	--	--	--	---	---	--	---	---	---	--

Ledertvernsnitt mm ²	Weight KG/100m	El nr.	Length pack meter
HF Coilfix Xpress 16mm	4,9	1251600	100
HF Coilfix Xpress 20mm	7,6	1251601	50
HF Coilfix Xpress 25mm	8,4	125160X	50
HF-COILFIX 16mm rør with pulling wire	4,9	1251642	100
HF-COILFIX 20mm rør with pulling wire	7,6	1251643	50
HF-COILFIX 25mm rør with pulling wire	8,4	125164X	50