

## AT-GS900/8

### Unmanaged Gigabit Ethernet Switches



#### AT-GS900/8

8 port 10/100/1000TX unmanaged switch

#### High Performance

Designed for medium enterprises and educational networks, the Allied Telesis AT-GS900 Series of unmanaged Gigabit switches delivers the high-speed and high-performance demanded by today's high-bandwidth applications such as video, graphics, and industrial design.

#### Flexibility

Available in 8, 16 and 24 port models, Allied Telesis lets you decide which size is best for your network. Reduces your cost by allowing you to only pay for the ports you need.

#### Simplified Installation

The AT-GS900 Series switches require minimal configuration and can be installed in minutes for use in network racks or on desktops. The 10/100/1000TX copper ports on the AT-GS900 Series are fully auto-negotiating, allowing the switches to connect to all other 10Mbps Ethernet, 100Mbps Fast Ethernet, or 1000Mbps Gigabit Ethernet devices. Equipped with MDI/MDIX ports for easy connection to other hubs and switches, the ATGS900 Series offers a natural migration path from legacy networks and a cost-effective introduction to Gigabit Ethernet. Finally, easy to read front panel LEDs show ongoing switch status and simplify troubleshooting.

#### Quality & Reliability

Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches every year, Allied Telesis offers proven reliability and industry recognized quality.

#### Applications

Connected to managed Gigabit switches such as the AT-9424M or the AT-9748TS/XP or unmanaged Fast Ethernet switches such as the AT-FS724L or the AT-LE700, the AT-GS900 Series remains the ideal fit for Gigabit migration in Local Area Networks (LANs). The AT-GS900 Series of unmanaged Gigabit switches can forward both standard sized packets and VLAN-tagged packets throughout LANs. For those applications requiring Gigabit to the desktop, an ideal design combines Allied Telesis AT-GS900 Series switches with any of our full line of Gigabit network adapter cards—whether it's the AT-2930T for copper Gigabit or the AT-2930SX for fiber Gigabit.

#### Key Features

- Wirespeed performance
- Non-blocking architecture
- Auto-negotiation Gigabit ports
- Auto MDI/MDIX on TX ports
- Transparent to VLAN packets
- Full duplex flow control
- Sturdy metal case

# AT-GS900/8 | Unmanaged Gigabit Ethernet Switches

## Performance

14,880pps for 10Mbps Ethernet  
148,800pps for 100Mbps Ethernet  
1,488,000pps for 1000Mbps Ethernet

Switching Capacity Up to 12Mpps

MAC Addresses Up to 4K

Packet Buffer 128KB

Half/Full duplex  
Auto-negotiation  
MDI/MDIX

## Interface Connections

10/100/1000TX RJ-45

## Power Characteristics

Voltage 100-240vAC  
Frequency 50/60Hz  
Current 0.3A  
Power Consumption Max 15W

## Environmental Specifications

Operating Temp. 0°C to 40°C (32°F to 104°F)  
Non-operating Temp. -25°C to 70°C (-13°F to 158°F)  
Operating Humidity 5% to 90% non-condensing  
Storage Humidity 5% to 95% non-condensing

## Technical Specifications

### Physical Characteristics

Dimensions 3.8 x 24.9 x 11.4 cm  
(1.5 x 9.80 x 4.49 in)

Weight .90kg (1.98lbs)

### Wall-mount or Desktop

All units come with Wall & 19" Rack mount brackets

## Standards & Compliance

IEEE 802.3 10T Ethernet  
IEEE 802.3u 100TX Fast Ethernet  
IEEE 802.3ab 1000T Gigabit Ethernet  
IEEE 802.3z Full duplex  
IEEE 802.3x Flow control

## Electrical/Mechanical Approvals

UL 1950  
FCC/EN55022 Class A  
VCCI Class A  
C-Tick  
EN60950 (TUV)  
EN55024  
CE

## Ordering Information

### AT-GS900/8

8 port 10/100/1000TX unmanaged switch

Where xx = 10 for U.S. power cord  
= 20 for no power cord  
= 30 for U.K. power cord  
= 40 for Australia power cord  
= 50 for Europe power cord

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-00572-00 Rev. C