



RRCB PLAIN COPPER ROUND BRAIDS

- **RRCB : Round Red Copper braids**
- The RRCB braids are mainly used for power distribution or earthing applications.



Part No	Description	Section (mm ²)	External Ø (mm)	Number of strands	Nominal current (A)		
557400	RRCB 15-6	6	4	352	45	25 m	0,06 kg
557410	RRCB 15-8	8	4,5	464	65	25 m	0,08 kg
557420	RRCB 15-10	10	5	560	75	25 m	0,10 kg
557430	RRCB 15-16	16	6	900	120	25 m	0,16 kg
557440	RRCB 15-25	25	8	1416	150	25 m	0,25 kg
557450	RRCB 15-30	30	9	1680	180	25 m	0,30 kg
557460	RRCB 15-50	50	11	2820	250	25 m	0,50 kg
557470	RRCB 15-75	75	14	4236	300	25 m	0,75 kg
557480	RRCB 15-100	100	18	5652	360	25 m	1,00 kg

□ **Technical data:**

- Plain copper round braids
- Electrolytic copper Cu-ETP according to standard NF EN 13601
- Copper purity of minimum 99,9%
- Maximum resistivity of 0,017241 Ωmm² / m at 20°C
- Standard wire diameter: 0,15 mm
- 25 m coils

□ **Certificates:**

- ROHS 2002/95/EC Compliance

