SIEMENS

Product data sheet 5SD7464-0

Similar to image

SURGE ARRESTER TYPE 2 REQUIREMENT CATEGORY C,
UC 350V PLUG-IN PROTECTION BLOCKS 4POLE,
3+1 CIRCUIT FOR TN-S AND TT SYSTEMS

Technical data:		
Type of mounting		DIN rail 35 mm
Protection level	kV	1.4
Type of the power supply network		4
Product component / remote-signaling contact		No
Size of the surge arrester		4 TE
Continuous operating voltage / with AC / maximum	V	350
Discharge current / at (8/20) µs / nominal value	kA	40
Type of distribution system		TN-S and TT
SPD classification / acc. to EN 61643-11 / test class II type 2		Yes
Signal design		optical
Product component / fuse		No
Operating voltage		
• with AC / nominal value	V	415
Protection level		
• between N and L	kV	1.4
• between PE and N and/or L	kV	1.5
Conductor cross section that can be connected		
• for rigid conductor		

subject to modifications
© Copyright Siemens AG 2013

• maximum	mm²	35
• minimum	mm²	1.5
• finely stranded		
• maximum	mm²	25
• minimum	mm²	1.5

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
GOST	EG-Konf.	Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/5SD7464-0/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD7464-0

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
Datanorm GAEB81 GAEB83 RTF TXT

subject to modifications
© Copyright Siemens AG 2013



last change: Mar 11, 2013

subject to modifications
© Copyright Siemens AG 2013