SIEMENS

Product data sheet 5SD8020

Similar to image

DIAZED FUSE-LINK 690V FOR CABLE AND LINE PROTECTION UTILIZATION CATEGORY GG SIZE DIII, E33, 20A

Technical data:		
Color coding of the fuse link		blue
Current / for AC / rated value	A	20
Tripping characteristic class		others
Size of the fallback-system / acc. to DIN EN 60269-1		DIII
Supply voltage		
• for AC / rated value	V	690
• for DC	V	600
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	50
• with DC / in accordance with IEC 60947-2 / rated value	kA	8
Ambient temperature		
• minimum	°C	-5
• maximum	°C	40

Certificates/approvals:

© Copyright Siemens AG 2013

General Product Approval	Declaration of Conformity	Test Certificates	other
GOST	EG-Konf.	Type Test Certificates/Test Report	Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/5SD8020/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SD8020

CAx-Online-Generator
http://www.siemens.com/cax



last change: Nov 4, 2012

© Copyright Siemens AG 2013