



RC UNIT FOR MCB 5SX6+7 TYPE A (PSE/SSF),  
DEPTH=70MM 80/100A 4 POLE IFN 30A 400V




Similar to image

**Technical data:**

|  |     |                              |
|--|-----|------------------------------|
| <b>mounting position</b>                                       |     | any                          |
| <b>Height</b>  | mm  | 90                           |
| <b>Width</b>   | mm  | 124                          |
| <b>Depth</b>   | mm  | 77                           |
| <b>Design of the product</b>                                   |     | Instantaneous                |
| <b>Supply voltage / for AC / rated value</b>                   | V   | 400                          |
| <b>Resistance against the impulse current / rated value</b>    | kA  | 1                            |
| <b>Ambient temperature</b>                                     | °C  | -25 ... +45                  |
| <b>Ambient temperature</b><br>• during storage                 | °C  | -40 ... +75                  |
| <b>Mechanical operating cycles as operating time / typical</b> |     | 10,000                       |
| <b>Overvoltage class</b>                                       |     | III                          |
| <b>Supply voltage / for testing equipment / minimum</b>        | V   | 100                          |
| <b>Protection against electrical shock</b>                     |     | Finger and back-of-hand safe |
| <b>Position / of power supply cord</b>                         |     | top or bottom                |
| <b>Tightening torque</b><br>• with screw-type terminals        | N·m | 2.5 ... 3                    |
| <b>Section de conducteur raccordable</b>                       |     |                              |

|  |                 |            |
|--|-----------------|------------|
| • solid  | mm <sup>2</sup> | 1.5 ... 25 |
| • multibrin  | mm <sup>2</sup> | 1.5 ... 25 |
| <b>Product feature</b>   |                 |            |
| • [not supplied - silicon-free]  |                 | Yes        |
| • halogen-free   |                 | Yes        |
| <b>Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30</b> |                 | 28         |
| <b>Device tag</b>  |                 |            |
| • according to DIN EN 61346-2  |                 | F          |
| • according to DIN EN 81346-2  |                 | F          |

#### Certificates/approvals:

| General Product Approval  | Declaration of Conformity  | other   |
|---|--|---|
| <br>GOST | <br>VDE | <br>EG-Konf. |
|   |  | <a href="#">Environmental Confirmations</a>   |

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SM2347-0/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SM2347-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2347-0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 4, 2013