

UNDERVOLTAGE RELEASE AC 230V, WITH 6 TERMINALS FOR LS-SWITCH 5SL4, 5SY, 5SP, RCBO 5SU1, RCD 5SV



**General technical data**

Switching function / ON-delay/instantaneous contact	No
Type of voltage / for actuation	AC

**Control current**

<b>Control supply voltage</b>	
• at AC / at 50 Hz / rated value / minimum	230 V
• at AC / at 50 Hz / rated value / maximum	230 V
• at AC / at 60 Hz / rated value / minimum	230 V
• at AC / at 60 Hz / rated value / maximum	230 V

**Suitability**

<b>Suitability for integration</b>	
• motor starter protector	No
• overload relay	No
<b>Suitability for use</b>	
• load switch	No
• circuit breaker	No

**Number**

Number of NC contacts	0
Number of NO contacts	2
Number of CO contacts	0

## Connections

Type of electrical connection	screw-type terminals
Declaration of Conformity	other



EG-Konf.

[Environmental Confirmations](#)

[Miscellaneous](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3040>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3040>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3040](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3040)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>



