

RCBO elm, 10 kA, 1P+N, type A, 30 mA, B-char, In: 16 A, Un AC: 230 V

Model	
Product brand name	SENTRON
Product designation	RCBO
Design of the product	Instantaneous
General technical data	
Number of poles	2
Number of poles / Note	1P+N
Number of poles / with protection	1
Tripping characteristic class	B
circuit-breaker / Design	5SU1
Mechanical service life (switching cycles) / typical	10 000
Overvoltage category	III
Voltage	
Surge current resistance / at (8/20) μ s	1 kA
Supply voltage	
Supply voltage	
<ul style="list-style-type: none"> at AC / rated value for testing equipment / minimum 	230 V 195 V
Supply voltage frequency / rated value	50 Hz
Protection class	
Protection class IP	IP20, if the distribution board is installed, with connected conductors
Energy limiting class	3
Switching capacity	
Switching capacity current	
<ul style="list-style-type: none"> acc. to EN 60898 / rated value acc. to IEC 60947-2 / rated value 	10 kA 20 kA
Dissipation	
Power loss [W]	
<ul style="list-style-type: none"> for rated value of the current / at AC / in hot operating state / per pole maximum 	3 W 6 W
Electricity	

Tripping residual current / rated value	30 mA
rated current I_n / IEC, DIN/VDE / at 40 Cel	15.2 A
Type of fault current	A
Current / at AC / rated value	16 A

Product details

Product feature / Touch protection	Yes
Product feature	
• halogen-free	Yes
• silicon-free	Yes

Product function

Product function / neutral conductor switching	Yes
--	-----

Number

Number of test cycles / for environmental testing / acc. to IEC 60068-2-30	26
---	----

Connections

Connectable conductor cross-section / stranded	
• minimum	0.75 mm ²
• maximum	35 mm ²
Connectable conductor cross-section	
• solid	
— minimum	0.75 mm ²
— maximum	35 mm ²
• finely stranded / with core end processing	
— minimum	0.75 mm ²
— maximum	25 mm ²
Tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
Position / of power supply cord	Either top or bottom

Mechanical Design

Height	90 mm
Width	36 mm
Depth	77 mm
Mounting position	any
Installation depth	70 mm
Number of width units	2
Net weight	281 g

Environmental conditions

Degree of pollution	2
Influence of the surrounding temperature	Max. 95% humidity

Ambient temperature

- | | |
|----------------------------|--------|
| • minimum | -25 °C |
| • maximum | 55 °C |
| • during storage / minimum | -40 °C |
| • during storage / maximum | 75 °C |

Certificates

Equipment marking

- | | |
|--------------------------|---|
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

General Product Approval



CCC



IMQ



ÖVE



VDE

[Miscellaneous](#)



RCM

Declaration of Conformity



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1354-6KK16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SU1354-6KK16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1354-6KK16

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>