

RCCB, 4-pole, type A, In: 80 A, 100 mA, Un AC: 400 V



Model	
Product brand name	SENTRON
Product designation	RCCB
Design of the product	Instantaneous
General technical data	
Number of poles	4
Size of installation devices / acc. to DIN 43880	1
Protection against electrical shock	Finger and back-of-hand safe
Short-circuit current rating	10 kA
circuit-breaker / Design	5SV3
Mechanical service life (switching cycles) / typical	10 000
Switching function / short-term delayed	No
Overvoltage category	III
Supply voltage	
Supply voltage	
<ul style="list-style-type: none"> <li>• at AC / rated value</li> <li>• for testing equipment / minimum</li> </ul>	<p>400 V</p> <p>100 V</p>
Supply voltage frequency	

- rated value

50 Hz

## Protection class

### Protection class IP

IP20, if the distribution board is installed, with connected conductors

## Switching capacity

Switching capacity current / according to IEC 61008-1 / rated value

0.8 kA

## Dissipation

### Power loss [W]

- for rated value of the current / at AC / in hot operating state / per pole

4.1 W

## Electricity

### Tripping residual current / rated value

100 mA

rated current  $I_n$  / IEC, DIN/VDE / at 40 Cel

80 A

### Type of fault current

A

Current / at AC / rated value

80 A

### I<sup>2</sup>t-value / permissible

44 880 A<sup>2</sup>·s

Surge current resistance / rated value

1 kA

## Product details

Product feature / silicon-free

Yes

Product extension / can be installed / supplementary devices

Yes

## Number

Number of test cycles / for environmental testing / acc. to IEC 60068-2-30

28

## Connections

### Connectable conductor cross-section / stranded

- minimum
- maximum

0.75 mm<sup>2</sup>

35 mm<sup>2</sup>

Connectable conductor cross-section / solid

- minimum
- maximum

0.75 mm<sup>2</sup>

35 mm<sup>2</sup>

### Tightening torque / with screw-type terminals

- minimum
- maximum

2.5 N·m

3 N·m

Position / of power supply cord

top or bottom

## Mechanical Design

### Height

90 mm

### Width

72 mm

### Depth

70 mm

Mounting position	any
Installation depth	70 mm
Number of width units	4
Mounting type	DIN rail (REG)
Net weight	350 g

#### Environmental conditions

##### Ambient temperature

- minimum -25 °C
- maximum 45 °C
- during storage / minimum permissible -40 °C
- during storage / maximum permissible 75 °C

#### Certificates

##### Equipment marking

- acc. to DIN EN 61346-2 F
- acc. to DIN EN 81346-2 F

#### General Product Approval



[Miscellaneous](#)

#### Declaration of Conformity



#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV3447-6>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV3447-6>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SV3447-6](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV3447-6)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>





