

CIRCUIT BREAKER 230/400V 25KA, 1POLE, C, 1.6A, D=70MM



| Model   |                           |
|---|---------------------------|
| Product brand name  | SENTRON                   |
| Product designation   | Miniature circuit breaker |
| General technical data  |                           |
| Number of poles   | 1                         |
| Number of poles / Note  | 1P                        |
| Tripping characteristic class   | C                         |
| characteristic / Let-through current characteristic   | DS_5SY_C_1_6              |
| circuit-breaker / Design  | 5SY8                      |
| Mechanical service life (switching cycles) / typical  | 20 000                    |
| Overvoltage category  | 3                         |
| Voltage   |                           |
| Type of voltage   | AC/DC                     |
| Insulation voltage  |                           |
| <ul style="list-style-type: none"> <li>with single-phase operation / at AC / rated value</li> </ul> | 250 V                     |
| <ul style="list-style-type: none"> <li>with multi-phase operation / at AC / rated value</li> </ul>  | 440 V                     |
| Supply voltage  |                           |

|                                      |          |
|--------------------------------------|----------|
| Supply voltage / at AC / rated value | 400 V    |
| <b>Supply voltage frequency</b>      |          |
| • rated value                        | 50/60 Hz |

|                              |                                 |
|------------------------------|---------------------------------|
| <b>Protection class</b>      |                                 |
| <b>Protection class IP</b>   | IP20, with connected conductors |
| <b>Energy limiting class</b> | 3                               |

|   |       |
|---|-------|
| <b>Switching capacity</b>                   |       |
| <b>Switching capacity current</b>           |       |
| • at DC / acc. to IEC 60947-2 / rated value | 15 kA |
| • acc. to IEC 60947-2 / rated value         | 70 kA |

|  |       |
|--|-------|
| <b>Dissipation</b>   |       |
| <b>Power loss [W]</b>  |       |
| • for rated value of the current / at AC / in hot operating state / per pole | 1.2 W |
| • maximum  | 1.2 W |

|  |                                   |
|--|-----------------------------------|
| <b>Electricity</b>   |                                   |
| rated current $I_n$ / IEC, DIN/VDE / at 40 Cel                     | 1.504 A                           |
| Current / at AC / rated value                                      | 1.6 A                             |
| <b>Current limitation characteristic, no. / Let-through energy</b> | DE_5SY_C_1_6                      |
| <b>Suitability for operation</b>                                   | Mechanical engineering / industry |

|  |     |
|--|-----|
| <b>Product details</b>                                       |     |
| Product feature / Touch protection                           | Yes |
| <b>Product component</b>                                     |     |
| • combined terminal top                                      | Yes |
| • combined terminal bottom                                   | Yes |
| <b>Product feature</b>                                       |     |
| • Properties for main switches in accordance with EN 60204-1 | Yes |
| • halogen-free   | Yes |
| • sealable   | Yes |
| • silicon-free   | Yes |
| Product extension / can be installed / supplementary devices | Yes |

|  |    |
|--|----|
| <b>Product function</b>                        |    |
| Product function / neutral conductor switching | No |

|   |      |
|---|------|
| <b>Short circuit</b>  |      |
| <b>Breaking capacity short-circuit current (I<sub>cn</sub>)</b> |      |
| • at AC / acc. to UL 1077 and CSA C22.2 No.235                  | 5 kA |

|               |  |
|---------------|--|
| <b>Number</b> |  |
|---------------|--|

|  |   |
|--|---|
| Number of test cycles / for environmental testing / acc. to IEC 60068-2-30 | 6 |
|--|---|

### Connections

|   |  |
|---|--|
| <b>Connectable conductor cross-section / stranded</b>   |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 0.75 mm <sup>2</sup><br>35 mm <sup>2</sup>   |
| <b>Connectable conductor cross-section</b>  |  |
| <ul style="list-style-type: none"> <li>• solid               <ul style="list-style-type: none"> <li>— minimum</li> <li>— maximum</li> </ul> </li> <li>• finely stranded / with core end processing               <ul style="list-style-type: none"> <li>— minimum</li> <li>— maximum</li> </ul> </li> </ul> | 0.75 mm <sup>2</sup><br>35 mm <sup>2</sup><br>0.75 mm <sup>2</sup><br>25 mm <sup>2</sup> |
| <b>AWG number / as coded connectable conductor cross section</b>  |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 14<br>4  |
| <b>Tightening torque [lbf·in] / with screw-type terminals</b>   |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 22 lbf·in<br>26 lbf·in   |
| <b>Tightening torque / with screw-type terminals</b>  |  |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 2.5 N·m<br>3 N·m   |
| Position / of power supply cord   | Any  |

### Mechanical Design

|                       |                       |
|-----------------------|-----------------------|
| Height                | 90 mm                 |
| Width                 | 18 mm                 |
| Depth                 | 76 mm                 |
| Mounting position     | any                   |
| Installation depth    | 70 mm                 |
| Number of width units | 1                     |
| Mounting type         | Quick assembly system |
| Net weight            | 159 g                 |

### Environmental conditions

|  |   |
|--|---|
| Degree of pollution  | 3   |
| Influence of the surrounding temperature   | Max. 95% humidity   |
| Vibration resistance / acc. to IEC 60068-2-6   | 50m/s <sup>2</sup> at 25 to 150Hz and 60m/s <sup>2</sup> at 35Hz (4sec) |
| <b>Ambient temperature</b>   |   |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> <li>• during storage / minimum</li> </ul> | -25 °C<br>55 °C<br>-40 °C   |

• during storage / maximum

75 °C

## Certificates

Equipment marking / acc. to DIN EN 61346-2

F

### General Product Approval

### Declaration of Conformity



UL

[Miscellaneous](#)



EG-Konf.

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SY8115-7>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SY8115-7>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SY8115-7](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY8115-7)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>



