

SWITCH 230/400V 1POLE 40A, T=70MM





Similar to image

### Technical data:

Number of poles		1
Design of the operating mechanism		toggle handle
Product equipment / interlock		No
Continuous current / rated value	A	40
Acceptability for application / emergency stop switch		No
Type from device		other
Design of the electrical connection / for main current circuit		screw-type terminals
Number of NC contacts / for auxiliary contacts		0
Acceptability for application / safety cut-out switch		No
Type of the driving mechanism / motor drive		No
Number of NO contacts / for auxiliary contacts		1
Number of change-over switches / for auxiliary contacts		0
Operating voltage / at 50/60 Hz / for AC / rated value	V	230
Protection class IP		IP20
Acceptability for application / main switch		No
Acceptability for application / switch disconnecter		Yes
Product extension / optional / motor drive		No
Product extension / optional / voltage trigger		No

Type of fixing / 4-hole front mounting		No
Type of fixing / central front mounting		No
Suitability for integration / distribution board		Yes
Acceptability for application / maintenance/repair switch		No

#### Certificates/approvals:

General Product Approval	Declaration of Conformity	other
 GOST	 EG-Konf.	<a href="#">Environmental Confirmations</a>

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TE2411-0/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TE2411-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE2411-0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Nov 5, 2012