

ISOLATOR 40A DOUBLE POLE



Similar to image

Technical data:

Mounting depth	mm	70
Operating voltage / rated value	V	440
Operating current / rated value	A	40
Type of voltage		AC
Number of poles		2
Breaking capacity current / rated value	kA	0.12
Resistance against short-circuit current	kA	10
Design of the switching function		Switch disconnecter
Number of width units		2
Number of NC contacts		0
Number of NO contacts		2
Number of change-over switches		0
Product component / Signal lamp		No
Product function / positive opening (acc. to DIN VDE 0113)		No

Certificates/approvals:



**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TL1240-0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5TL1240-0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TL1240-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL1240-0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Sep 1, 2014