

ALPHA DIN, COPPER BUSBARS 12X5MM, 250A,
W=500



Similar to image

Technical data:

| | | |
|--|----|--------|
| Busbar design | | others |
| Length | mm | 500 |
| Width | mm | 12 |
| Operating current / rated value | A | 250 |
| Thickness / of busbar | mm | 5 |
| Material / of the busbar | | Cu |
| Product property / flexible | | No |
| Traitement de surface / étamé | | No |

Certificates/approvals:

General Product Approval

Declaration of Conformity

Test Certificates



GOST



EG-Konf.

[Type Test Certificates/Test Report](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8GK9731-0KK20/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK9731-0KK20

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Nov 29, 2012