

PEN TERM. THERMOPLASTIC PA6.6 SCREW TERMINAL  
ON BOTH ENDS GREEN-YELLOW,  
12MM, SZ16



Similar to image

**Technical data:**

<b>Type of mounting</b>		DIN rail 35 mm
<b>Length</b>	mm	53
<b>Color</b>		green-yellow
<b>Height of lowest mounting type</b>	mm	38
<b>Number of terminal levels</b>		2
<b>Number of terminal points / per terminal level</b>		1
<b>Product feature / PEN function</b>		Yes
<b>Combustibility class acc. to UL 94</b>		V2
<b>Terminal contact spacing</b>	mm	12
<b>Position / of terminal</b>		lateral
<b>Product component / required / connection plate</b>		No
<b>Ambient temperature / during operating</b>		
• minimum	°C	-25
• maximum	°C	55
<b>Design of the electrical connection</b>		
• 1		screw-type terminal
• 2		screw-type terminal
<b>Conductor cross-section that can be connected</b>		

- solid
  - maximum
- multibrin
  - maximum
- finely stranded
  - with wire end processing
    - maximum
  - without wire end processing
    - maximum

mm <sup>2</sup>	16
mm <sup>2</sup>	16
mm <sup>2</sup>	16
mm <sup>2</sup>	16

**Certificates/approvals:**

**General Product Approval**



**other**

[Environmental Confirmations](#)

**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/mall>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WWW/view/en/8WA1011-1PK00/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WA1011-1PK00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1PK00)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**last change:**

Mar 11, 2013