

PLUG-IN RELAY, 3 CO CONTACTS, WITH LED, 115V AC, 10A, WIDTH 38MM, MT RANGE



General technical data:

Supply voltage frequency for auxiliary and control current circuit rated value		
• minimum	Hz	50
• maximum	Hz	60
<b>Type of voltage</b>		AC
<b>Control supply voltage</b>		
• at AC		
— at 50 Hz rated value		
— minimum	V	115
— maximum	V	115
— at 60 Hz rated value		
— minimum	V	115
— maximum	V	115
Number of NC contacts for auxiliary contacts		0
Number of NO contacts for auxiliary contacts		0
Number of CO contacts for auxiliary contacts		3
Operating current of auxiliary contacts		
• at AC-15		

— at 230 V

	A	5
Design of the switching function positively driven		No
Switching behavior		monostable

#### Mechanical data:

Type of electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component Plug-in socket		No
Width	mm	35.5
Height	mm	36.5
Depth	mm	69

#### Certificates/ approvals:

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[Confirmation](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZX:MT328115>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/LZX:MT328115>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=LZX:MT328115&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZX:MT328115&lang=en)

last modified:

08/12/2017