

PLUG-IN RELAY, 4 CO CONTACTS, 115V AC, 6A,  
WIDTH 22.5MM



General technical data:





Supply voltage frequency for auxiliary and control current circuit rated value		
• minimum	Hz	50
• maximum	Hz	60
<b>Type of voltage</b>		AC
<b>Control supply voltage</b>		
• at AC		
— at 50 Hz rated value		
— minimum	V	115
— maximum	V	115
— at 60 Hz rated value		
— minimum	V	115
— maximum	V	115
Number of NC contacts for auxiliary contacts		0
Number of NO contacts for auxiliary contacts		0
Number of CO contacts for auxiliary contacts		4
Operating current of auxiliary contacts		
• at DC-13		

— at 24 V	A	4
• at AC-15		
— at 230 V	A	4
<b>Design of the switching function positively driven</b>		No
<b>Switching behavior</b>		monostable

#### Mechanical data:

<b>Type of electrical connection</b>		screw-type terminals
<b>Design of the relay operating mechanism</b>		poled
<b>Product component Plug-in socket</b>		No
<b>Width</b>	mm	22.5
<b>Height</b>	mm	28
<b>Depth</b>	mm	35

#### Certificates/ approvals:

General Product Approval	Declaration of Conformity	other
 UR	 VDE	 EAC
	 EG-Konf.	<a href="#">Confirmation</a>

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZX:PT570615>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/LZX:PT570615>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=LZX:PT570615&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZX:PT570615&lang=en)

last modified:

08/12/2017